



## LED Blowfish Black E27 DIM 4W (11W) 100lm 922

LED lempa

10022

*Bailey Blowfish Black LED E27 4W 2200K 100lm (11W) Dimmable 230V-240V 922 360D 167x174mm LED Filament deco lamp*

*With the Bailey Blowfish LED filament lamp from the Designs by Bailey Lights series, the Bailey designers have created a piece of art. Just as the Blowfish is unique in real life, it is also in the shape of this lamp. For this patented lamp, all spines are applied by hand. Not only is this very labor-intensive, but it also gives a magnificent effect when the lamp is on. When the lamp is not lit, it is also a pearl in the interior. It has a regular E27 fitting so that it can be placed in practically all lamp holders and pendants. Of course you can combine it with the Bailey accessories or place it in the so called cage fixtures. The lamp provides you with warm light (2200K), it uses little energy (4W) and it has a long life-time. Which make it a truly sustainable product. The Bailey Bird is dimmable (recommended dimmer Bailey WW15031 dimmer).*

## KLASIFIKACIJA

Grupė	Lempos
Klasė	Šviesos diodų lempos
Pavadinimas	LED Blowfish Black E27 DIM 4W (11W) 100lm 922
Gamintojas	BAI
Serija	Designs by Bailey lights
Tipas	Bailey Blowfish
EAN	8714681438695
Gamintojo kodas	143869

## PARAMETRAI

Lizdas	E27
Lempos galia [W]	4 - 4
Nominali įtampa [V]	220 - 240
Įtampos tipas	AC
Nominali srovė [mA]	18 - 18

Lempos forma	Rutulys
Spalvinė temperatūra [K]	2200 - 2200
Šviesos spalva	822 - 822
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	100 - 100
Lempos efektyvumas [lm/W]	25
Spinduliavimo kampas [°]	360
Ilgis [mm]	174
Energetinio efektyvumo klasė	G
Energetinio efektyvumo indeksas (EEI)	0.29
Energijos sąnaudos 1000 h [kWh]	4
Spalvinė temperatūra pagal EN 12464-1	Šiltai balta mažiau nei 3300 K
Siūlelinio tipo leputės	Taip
Vidutinis tarnavimo laikas [h]	15000
Spalvos atitikimas (McAdamo elipsė)	SDCM6
Korpuso spalva	Juoda
Apsaugos klasė (IP)	IP20
Reguliuojama	00000
Reguliuojama	Taip
Paskirtis	Kita
Minimalus įjungimo ciklų skaičius	15000
Fotobiologinė sauga pagal EN 62471	RG1
Galios faktorius	0.85
Valdymo galimybė	Ne
Stiklo gaubto tipas	Skaidri
Su nuotolinio valdymo pulteliu	Ne