

TUN LED 2D 4P GR10q 12.5W 827 CCG

LED lempa

10121



TUN LED 2D Lamp GR10q 4pin 12.5W 2700K Opal 1400lm
230V/AC 23x201mm CCG Direct retrofit 28W 2pin Magnetic
ballast

Tungsrām's LED 2D lamps offer safe, reliable and affordable energy saving alternatives to CFL 2D lamps used in bulkhead fixtures. Tungsrām's new LED 2D lamps can offer direct retrofit replacement for 16W 2Pin 2D lamps operated on Magnetic ballast, 28W 4Pin 2D lamps operated on Magnetic and Electronic ballast (separate designs). This replacement can be completed simply without tools or costly upgrade and the robust middle part will ensure easy handle during installation. The upgraded fixture will deliver huge energy saving and reduced operating cost driven by the increased life and the classic 2D shape with great light distribution will ensure satisfaction for end-users.

KLASIFIKACIJA

Grupē	Lempos
Klasē	Šviesos diodų lempos
Pavadinimas	TUN LED 2D 4P GR10q 12.5W 827 CCG
Gamintojas	Tungsrām
Serija	LED 2D
Tipas	TUN LED 4 Pin
EAN	5994100028345
Gamintojo kodas	93110762

PARAMETRAI

Lizdas	Kita
Lempos galia [W]	12.5 - 12.5
Nominali ģtampa [V]	230 - 230
Ģtampos tipas	AC
Nominali srovē [mA]	57 - 57
Lempos forma	Kita
Spalvinē temperatūra [K]	2700 - 2700

Šviesos spalva	827 - 827
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	1400 - 1400
Lempos efektyvumas [lm/W]	112
Spinduliavimo kampas [°]	120
Diametras [mm]	23
Ilgis [mm]	201
Energetinio efektyvumo klasė	A+
Energijos sąnaudos 1000 h [kWh]	12.5
Spalvinė temperatūra pagal EN 12464-1	Šiltai balta mažiau nei 3300 K
Siūlelinio tipo leputės	Ne
Vidutinis tarnavimo laikas [h]	40000
Spalvos atitikimas (McAdamo elipsė)	SDCM6
Korpuso spalva	Balta
Apsaugos klasė (IP)	IP20
Reguliuojama	Ne
Paskirtis	Kita
Minimalus įjungimo ciklų skaičius	50000
Fotobiologinė sauga pagal EN 62471	Kita
Valdymo galimybė	Ne
Stiklo gaubto tipas	Baltas
Su nuotolinio valdymo pulteliu	Ne