

LEDinspect MINI 250 LEDIL401

Rankinis šviestuvas

10129

OSR LED Inspection Luminaire Mini 250 LEDIL401
200X56x41mm 6000K 250/130lm 3.7V USB-C rechargeable



This high-quality inspection light from OSRAM is perfect for professional and private use. With three light functions - high with up to 250lm, low with up to 130lm and torchlight function with up to 70lm, there is a light output to suit the task at hand. The 180° flex base gives further flexibility to be able to adjust the lightbeam where needed. The inspection light is rechargeable, and the integrated charge level indicator shows the current status of the battery with up to 3h operating time at high power or up to 6h at low power. A USB Type-C charging cable and the corresponding power adaptor are included in the scope of supply. In accordance with IP65 protection rating, this inspection light has protection against dust and water ingress and is tested for impact resistance in accordance with IK07. This LED light is easy to carry, has a non-slip and dirt-repellent surface, includes an integrated hook & magnets for hands-free work and easy attachment.

KLASIFIKACIJA

Grupė	Šviestuvai
Klasė	Rankiniai šviestuvai
Pavadinimas	LEDinspect MINI 250 LEDIL401
Gamintojas	OSRAM
Serijs	LEDinspect
Tipas	MINI LEDIL401
EAN	4052899623828
Gamintojo kodas	4052899623828

PARAMETRAI

Maksimalus sistemos galingumas [W]	7.4
Nominali įtampa [V]	3.7 - 3.7
Įtampos tipas	DC
Spalvinė temperatūra [K]	6000 - 6000

Šviesos spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Vardinis šviesos srautas pagal IEC 62722-2-1 [lm]	250
Ilgis [mm]	200
Plotis [mm]	56
Įmontuotos lempos energetinio efektyvumo klasė	A++, A+, A (LED)
Lempos tipas	Nekeičiamas LED
Apsaugos klasė (IP)	IP65
Aukštis/gylis [mm]	41
Elektroapsaugos klasė	III
Tinka sekančio galingumo lempoms [W]	7.4 - 7.4
Tinka sekančiam lempų kiekiui	2
Su CEE kištuku	Ne
Su pajungimo kabeliu ir kištuku	Ne
Su šviesos šaltiniu	Taip
Su apsauginiu gaubtu	Ne
Su jungikliu	Taip