



LED Blowfish Gold E27 DIM 4W (17W) 160lm 919

LED lempa

10300

Bailey Blowfish Gold LED E27 4W 1900K 160lm (17W) Dimmable 230V-240V 919 360D 167x174mm LED Filament deco lamp

With the Bailey Blowfish LED filament lamp from the Designs by Bailey Lights series, the Bailey designers have created a piece of art. Just as the Blowfish is unique in real life, it is also in the shape of this lamp. For this patented lamp, all spines are applied by hand. Not only is this very labor-intensive, but it also gives a magnificent effect when the lamp is on. When the lamp is not lit, it is also a pearl in the interior. It has a regular E27 fitting so that it can be placed in practically all lamp holders and pendants. Of course you can combine it with the Bailey accessories or place it in the so called cage fixtures. The lamp provides you with warm light (2200K), it uses little energy (4W) and it has a long life-time. Which make it a truly sustainable product. The Bailey Bird is dimmable (recommended dimmer Bailey WW15031 dimmer).

KLASIFIKACIJA

| | |
|-----------------|--|
| Grupė | Lempos |
| Klasė | Šviesos diodų lempos |
| Pavadinimas | LED Blowfish Gold E27 DIM 4W (17W) 160lm 919 |
| Gamintojas | BAI |
| Serija | Designs by Bailey lights |
| Tipas | Bailey Blowfish |
| EAN | 8714681438688 |
| Gamintojo kodas | 143868 |

PARAMETRAI

| | |
|---------------------|-----------|
| Lizdas | E27 |
| Lempos galia [W] | 4 - 4 |
| Nominali įtampa [V] | 220 - 240 |
| Įtampos tipas | AC |
| Nominali srovė [mA] | 18 - 18 |

| | |
|---------------------------------------|--------------------------------|
| Lempos forma | Rutulys |
| Spalvinė temperatūra [K] | 1900 - 1900 |
| Šviesos spalva | 919 - 919 |
| Spalva | Balta |
| Spalvų atkūrimo koeficientas CRI | 90-100 |
| Šviesos srautas [lm] | 160 - 160 |
| Lempos efektyvumas [lm/W] | 40 |
| Spinduliavimo kampas [°] | 360 |
| Diametras [mm] | 167 |
| Ilgis [mm] | 174 |
| Energetinio efektyvumo klasė | G |
| Energetinio efektyvumo indeksas (EEI) | 0.18 |
| Energijos sąnaudos 1000 h [kWh] | 4 |
| Spalvinė temperatūra pagal EN 12464-1 | Šiltai balta mažiau nei 3300 K |
| Siūlelinio tipo leputės | Taip |
| Vidutinis tarnavimo laikas [h] | 15000 |
| Spalvos atitikimas (McAdamo elipsė) | SDCM6 |
| Korpuso spalva | Kita |
| Apsaugos klasė (IP) | IP20 |
| Reguliuojama | Taip |
| Paskirtis | Kita |
| Minimalus įjungimo ciklų skaičius | 15000 |
| Fotobiologinė sauga pagal EN 62471 | RG1 |
| Galios faktorius | 0.8 |
| Valdymo galimybė | Ne |
| Stiklo gaubto tipas | Skaidri |
| Su nuotolinio valdymo pulteliu | Ne |