



## LEDinspect POCKET PRO 400 LEDIL409

Rankinis šviestuvas

10413

OSR LED Inspection Luminaire Pocket Pro 400 LEDIL409  
215X100X55mm 6000K 400lm 3.7V rechargeable battery

The POCKET PRO 400 combines a slim design with multi-axis rotation and tilting so that the light can be directed exactly where it is needed. Additionally, the flexible mounting options offer hands-free working. The pocket size with only 6mm depth and the low weight make this inspection light ideal for the workshop. This LED inspection light emits up to 400 lumens. It has a white light with up to 6000K for comfortable working conditions and is therefore designed for wide illumination as well as for the illumination of narrow spaces. The light intensity can be easily adjusted via the on/off switch. In addition, the POCKET PRO 400 has a powerful torch for a concentrated beam of light. It is rechargeable and cordless, with Li-ion battery for constant light output. The lamp has an operating time of up to 3h and a recharging time of approx. 4h. Charging cable and mains plug included.

## KLASIFIKACIJA

|                 |                                    |
|-----------------|------------------------------------|
| Grupė           | Šviestuvai                         |
| Klasė           | Rankiniai šviestuvai               |
| Pavadinimas     | LEDinspect POCKET PRO 400 LEDIL409 |
| Gamintojas      | OSRAM                              |
| Serija          | LEDinspect                         |
| Tipas           | POCKETPRO LEDIL409                 |
| EAN             | 4052899622906                      |
| Gamintojo kodas | 4052899622906                      |

## PARAMETRAI

|                                    |             |
|------------------------------------|-------------|
| Maksimalus sistemos galingumas [W] | 9.62        |
| Nominali įtampa [V]                | 3.7 - 3.7   |
| Įtampos tipas                      | DC          |
| Spalvinė temperatūra [K]           | 6000 - 6000 |

|   |                  |
|---|------------------|
| Šviesos spalva                                    | Balta            |
| Spalvų atkūrimo koeficientas CRI                  | 80-89            |
| Vardinis šviesos srautas pagal IEC 62722-2-1 [lm] | 400              |
| Ilgis [mm]  | 215              |
| Plotis [mm]                                       | 100              |
| Įmontuotos lempos energetinio efektyvumo klasė    | A++, A+, A (LED) |
| Lempos tipas                                      | Nekeičiamas LED  |
| Apsaugos klasė (IP)                               | IP20             |
| Aukštis/gylis [mm]                                | 55               |
| Elektroapsaugos klasė                             | III              |
| Tinka sekančio galingumo lempoms [W]              | 9.62 - 9.62      |
| Tinka sekančiam lempų kiekiui                     | 2                |
| Su CEE kištuku                                    | Ne               |
| Su pajungimo kabeliu ir kištuku                   | Ne               |
| Su šviesos šaltiniu                               | Taip             |
| Su apsauginiu gaubtu                              | Ne               |
| Su jungikliu                                      | Taip             |