



LED Corn Compact E40 54W 8200lm 6500K 100V-260V

LED lempa

11211

BAI LED Corn Compact E40 54W 6500K 8200lm 100V-260V
360° 85x253mm IP64 120V-130V 230V-240V DISCONNECT
BALLAST

As a high-power LED lamp in a compact housing, the LED Corn Compact is the ideal retrofit replacement for, among other things, energy-saving lamps, incandescent lamps, mercury vapor lamps and metal halide lamps in both indoor and outdoor applications such as: street lighting and parking lot lighting, indoor applications where there is a high ceiling or a large room needs to be illuminated (warehouse, church, classroom, hall, etc.). After all, sustainability is not only about replacing old light sources with a more energy-efficient variant, but also about reusing existing fixtures. Very good price-quality ratio. Installation: disconnect the ballast before use. AC 100-260V 50 / 60Hz. Burning position: universal. Only suitable for temperatures up to 40°C inside the fixture. The LED light source can quickly malfunction due to overheating. Therefore not suitable for use in tight fixtures or fixtures where the reflector is close to the LED Corn. Recommended to remove glass or cover.

Pastaba:

- Kaip apsaugą nuo viršįtampių iki 10kV, siūlome naudoti ribotuvą kodu 78265.

KLASIFIKACIJA

Grupė	Lempos
Klasė	Šviesos diodų lempos
Pavadinimas	LED Corn Compact E40 54W 8200lm 6500K 100V-260V
Gamintojas	BAI
Serija	LED Corn
Tipas	Compact
EAN	8714681459454
Gamintojo kodas	145945

PARAMETRAI

Lizdas	E40
Lempos galia [W]	54 - 54

Nominali įtampa [V]	100 - 260
Įtampos tipas	AC
Nominali srovė [mA]	600 - 600
Lempos forma	Vamzdis su jungtimi 1 gale
Spalvinė temperatūra [K]	6500 - 6500
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	8200 - 8200
Spalvinė temperatūra pagal EN 12464-1	Neutrali balta 3300-5300 K
Lempos efektyvumas [lm/W]	152
Spinduliavimo kampas [°]	360 - 360
Diametras [mm]	85
Ilgis [mm]	253
Energetinio efektyvumo klasė	D
Energetinio efektyvumo indeksas (EEI)	90
Siūlelinio tipo leputės	Ne
Energijos sąnaudos 1000 h [kWh]	54
Vidutinis tarnavimo laikas [h]	35000
Spalvos atitikimas (McAdamo elipsė)	SDCM6
Korpuso spalva	Balta
Apsaugos klasė (IP)	IP64
Reguliuojama	Ne
Paskirtis	Kita
Minimalus įjungimo ciklų skaičius	15000
Fotobiologinė sauga pagal EN 62471	RG0
Galios faktorius	0.9
Valdymo galimybė	Ne
Stiklo gaubto tipas	Skaidri
Su nuotolinio valdymo pulteliu	Ne
Galimas IFTTT palaikymas	Ne
Suderinama su Amazon Alexa	Ne
Suderinama su Google Assistant	Ne
Suderinama su Apple HomeKit	Ne