



LED FIL Safe G45 E27 2W (12W) 100lm 822 PC Gold

LED lempa

11371

BAI LED Filament Safe Ball G45 E27 2W (12W) 100lm 2200K Gold 230V-240V 320° 45x70mm P45 IP44 Shatterproof PET Party LED-lamp

The LED filament Safe series responds to the desire to also use the decorative filament bulbs where shards are extremely undesirable when broken. Think of professional (open) kitchens, above tables in a restaurant, above the food department in and on the market. The bulb is made of polycarbonate which is much stronger than the traditional glass shade and also does not splinter. This also makes the lamp ideal for use in Bailey Light Strings at (temporary) festivals or events. When mounted hanging in combination with a suitable lamp holder (holder makes a watertight seal with the bulb) also outdoors applicable. We advise to use this lamp in combination with the Bailey Light Strings of 5, 10, 25 or 50m. Moreover, this lamp is durable and energy efficient.

KLASIFIKACIJA

| | |
|-----------------|---|
| Grupė | Lempos |
| Klasė | Šviesos diodų lempos |
| Pavadinimas | LED FIL Safe G45 E27 2W (12W) 100lm 822 PC Gold |
| Gamintojas | BAI |
| Serija | LED Filament safe |
| Tipas | G45 |
| EAN | 8714681457085 |
| Gamintojo kodas | 145708 |

PARAMETRAI

| | |
|--------------------------|-------------|
| Lizdas | E27 |
| Lempos galia [W] | 2 - 2 |
| Nominali įtampa [V] | 220 - 240 |
| Įtampos tipas | AC |
| Nominali srovė [mA] | 15 - 15 |
| Lempos forma | Rutulys |
| Spalvinė temperatūra [K] | 2200 - 2200 |

| | |
|---------------------------------------|--------------------------------|
| Spalva | Balta |
| Spalvų atkūrimo koeficientas CRI | 80-89 |
| Šviesos srautas [lm] | 100 - 100 |
| Spalvinė temperatūra pagal EN 12464-1 | Šiltai balta mažiau nei 3300 K |
| Lempos efektyvumas [lm/W] | 50 |
| Spinduliavimo kampas [°] | 320 - 320 |
| Diametras [mm] | 45 |
| Ilgis [mm] | 70 |
| Energetinio efektyvumo klasė | G |
| Siūlelinio tipo leputės | Taip |
| Energijos sąnaudos 1000 h [kWh] | 2 |
| Vidutinis tarnavimo laikas [h] | 10000 |
| Spalvos atitikimas (McAdamo elipsė) | SDCM6 |
| Korpuso spalva | Nespalvotas |
| Apsaugos klasė (IP) | IP44 |
| Reguliuojama | Ne |
| Paskirtis | Kita |
| Minimalus įjungimo ciklų skaičius | 7500 |
| Fotobiologinė sauga pagal EN 62471 | Kita |
| Galios faktorius | 0.5 |
| Valdymo galimybė | Ne |
| Stiklo gaubto tipas | Skaidri |
| Su nuotolinio valdymo pulteliu | Ne |
| Galimas IFTTT palaikymas | Ne |
| Suderinama su Amazon Alexa | Ne |
| Suderinama su Google Assistant | Ne |
| Suderinama su Apple HomeKit | Ne |