

LED Spot AR111 Glass GU10 DIM 15W (100W) 1200lm 930 25D

LED lempa

11992



BAI BaiSpot LED AR111 GU10 15W 3000K 25° Glass Reflector 1200lm (100W) Dimmable Ra90 230V-240V 111x69mm ES111 LED-lamp

The so-called LED spots from the BaiSpot series are characterized by a much longer lifespan and significantly less energy consumption than their halogen predecessors. Due to the compact design, they are easily interchangeable. This version has a high CRI value (color rendering index) of 90. Spots are mainly used to provide directed light from the ceiling or wall. This glass version literally and figuratively has an extra beautiful appearance because the part through which the light shines is made entirely of glass. Ambient temperature range: -20°C to +40°C.

KLASIFIKACIJA

Grupė	Lempos
Klasė	Šviesos diodų lempos
Pavadinimas	LED Spot AR111 Glass GU10 DIM 15W (100W) 1200lm 930 25D
Gamintojas	BAI
Serija	BaiSpot LED MV
Tipas	AR111 Glass
EAN	8714681464700
Gamintojo kodas	146470

PARAMETRAI

Lizdas	GU10
Lempos galia [W]	15 - 15
Nominali įtampa [V]	220 - 240
Įtampos tipas	AC
Nominali srovė [mA]	66 - 66
Lempos forma	Reflektorinė
Spalvinė temperatūra [K]	3000 - 3000
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	90-100

Šviesos srautas [lm]	1200 - 1200
Šviesos intensyvumas [cd]	3200
Spalvinė temperatūra pagal EN 12464-1	Šiltai balta mažiau nei 3300 K
Lempos efektyvumas [lm/W]	80
Spinduliavimo kampas [°]	25 - 25
Diametras [mm]	111
Ilgis [mm]	69
Energetinio efektyvumo klasė	F
Siūlelinio tipo leputės	Ne
Energijos sąnaudos 1000 h [kWh]	15
Vidutinis tarnavimo laikas [h]	15000
Spalvos atitikimas (McAdamo elipsė)	SDCM6
Korpuso spalva	Nespalvotas
Apsaugos klasė (IP)	IP20
Reguliuojama	Taip
Paskirtis	AR111
Minimalus įjungimo ciklų skaičius	30000
Fotobiologinė sauga pagal EN 62471	RG1
Galios faktorius	0.9
Valdymo galimybė	Ne
Stiklo gaubto tipas	Skaidri
Su nuotolinio valdymo pulteliu	Ne
Galimas IFTTT palaikymas	Ne
Suderinama su Amazon Alexa	Ne
Suderinama su Google Assistant	Ne
Suderinama su Apple HomeKit	Ne
Vardinis šviesos srautas pagal IEC 62612 [lm]	1200