



LED Corn Switch E27
9W-12W-18W
2200K-4000K
1000lm-2350lm

LED lempa

11997

BAI LED Corn Switch E27 3CCT 9W=1000lm 12W=1500lm 18W=2350lm 2200K 2700K 4000K 100V-260V 360° 60x155mm IP64 120V-130V 230V-240V DISCONNECT BALLAST

Sustainability is not only about replacing old light sources with a more energy-efficient version, but also about reusing existing fixtures. It is even more sustainable when 9 different versions are combined in 1 product. This saves on transport and storage. The special thing about the Switch series is that by simply adjusting a switch, the power (9W, 12W or 18W) and the light color can change (3000K, 4000K or 5000K). That's Smart and Green Thinking. Installation: disconnect the ballast before use. AC 100-260V 50/60Hz. Burning position: universal. Only suitable for temperatures up to 45°C inside the fixture. The LED light source can quickly malfunction due to overheating. Therefore not suitable for use in tight fixtures or fixtures where the reflector is close to the LED Corn. Recommended to remove glass or cover from the fixture.

Pastaba:

- Kaip apsaugą nuo viršįtampių iki 10kV, siūlome naudoti ribotuvą EAN kodu 8714681404409.

KLASIFIKACIJA

Grupė	Lempos
Klasė	Šviesos diodų lempos
Pavadinimas	LED Corn Switch E27 9W-12W-18W 1000lm-2350lm 2200K-4000K
Gamintojas	BAI
Serija	LED Corn
Tipas	Switch
EAN	8714681464519
Gamintojo kodas	146451

PARAMETRAI

Lizdas	E27
Lempos galia [W]	9 - 18
Nominali įtampa [V]	100 - 260

Įtampos tipas	AC
Nominali srovė [mA]	200 - 200
Lempos forma	Vamzdis su jungtimi 1 gale
Spalvinė temperatūra [K]	2200 - 4000
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	1000 - 2350
Spalvinė temperatūra pagal EN 12464-1	Šiltai balta mažiau nei 3300 K
Lempos efektyvumas [lm/W]	130
Spinduliavimo kampas [°]	360 - 360
Diametras [mm]	60
Ilgis [mm]	155
Energetinio efektyvumo klasė	E
Siūlelinio tipo leputės	Ne
Energijos sąnaudos 1000 h [kWh]	18
Vidutinis tarnavimo laikas [h]	35000
Spalvos atitikimas (McAdamo elipsė)	SDCM6
Korpuso spalva	Balta
Apsaugos klasė (IP)	IP64
Reguliuojama	Ne
Paskirtis	Kita
Minimalus įjungimo ciklų skaičius	12000
Fotobiologinė sauga pagal EN 62471	RG0
Galios faktorius	0.9
Valdymo galimybė	Ne
Stiklo gaubto tipas	Skaidri
Su nuotolinio valdymo pulteliu	Ne
Galimas IFTTT palaikymas	Ne
Suderinama su Amazon Alexa	Ne
Suderinama su Google Assistant	Ne
Suderinama su Apple HomeKit	Ne