



LED PL Glass TC-D G24d 2P 4.5W (10W) 580lm 830 EM+AC

LED lempa

12020

BAI LED PL Glass G24d 2-pins TC-D 4.5W (10W) 3000K Frosted 580lm 230V-240V 360° 34x109mm Temp. -20°C +45°C LED-lamp Alt PLC Dulux D

The LED PL Glass G24 (2-pin) TC-D lamps are replacements for the often used compact fluorescent lamps without integrated ballast. PL stands for Public as these lamps are mainly used in public spaces, corridors, offices and as orientation lighting. This PL LED series has the same shape and size as its fluorescent predecessors. In addition, just like their predecessor, they are made of glass, which ensures the same uniform light image. They are therefore a 1-on-1 sustainable replacements. Connect directly to mains voltage (AC). Not for use with Electronic Ballast (HF/ECG), disconnect ballast before use! Disconnecting magnetic ballast is optional, not necessary. Always read the manual carefully before installation. Ambient temperature range: -20°C to +40°C.

KLASIFIKACIJA

Grupė	Lempos
Klasė	Šviesos diodų lempos
Pavadinimas	LED PL Glass TC-D G24d 2P 4.5W (10W) 580lm 830 EM+AC
Gamintojas	BAI
Serija	LED PL
Tipas	G24d 2P Glass
EAN	8714681463116
Gamintojo kodas	146311

PARAMETRAI

Lizdas	G24d
Lempos galia [W]	4.5 - 4.5
Nominali įtampa [V]	220 - 240
Įtampos tipas	AC
Nominali srovė [mA]	38 - 38
Lempos forma	Vamzdis su jungtimi 1 gale

Spalvinė temperatūra [K]	3000 - 3000
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	580 - 580
Spalvinė temperatūra pagal EN 12464-1	Šiltai balta mažiau nei 3300 K
Lempos efektyvumas [lm/W]	128
Spinduliavimo kampas [°]	360 - 360
Diametras [mm]	34
Ilgis [mm]	109
Energetinio efektyvumo klasė	E
Siūlelinio tipo leputės	Ne
Energijos sąnaudos 1000 h [kWh]	5
Vidutinis tarnavimo laikas [h]	30000
Spalvos atitikimas (McAdamo elipsė)	SDCM5
Korpuso spalva	Balta
Apsaugos klasė (IP)	IP20
Reguliuojama	Ne
Paskirtis	Kita
Minimalus įjungimo ciklų skaičius	15000
Fotobiologinė sauga pagal EN 62471	RG0
Galios faktorius	0.5
Valdymo galimybė	Ne
Stiklo gaubto tipas	Baltas
Su nuotolinio valdymo pulteliu	Ne
Galimas IFTTT palaikymas	Ne
Suderinama su Amazon Alexa	Ne
Suderinama su Google Assistant	Ne
Suderinama su Apple HomeKit	Ne
Vardinis šviesos srautas pagal IEC 62612 [lm]	580