



## LED PL Glass TC-S G23 2P 4.5W (9W) 530lm 830 EM+AC

LED lempa

12095

BAI LED PL Glass G23 2-pins TC-S 4.5W (9W) 3000K Frosted 530lm 230V-240V 270° 32x159mm Temp. -20°C +45°C LED-lamp Alt PLS Dulux S

The LED PL Glass G23 (2-pin) TC-S lamps are replacements for the often used compact fluorescent lamps without integrated ballast. PL stands for PubLiC as these lamps are mainly used in public spaces, corridors, offices and as orientation lighting. This PL LED series has the same shape and size as its fluorescent predecessors. In addition, just like their predecessor, they are made of glass, which ensures the same uniform light image. They are therefore a 1-on-1 sustainable replacements. Installation: Disconnecting magnetic ballast is optional, not necessary. Not suitable for series connection and for for electronic ballast. Always read the manual carefully before installation. Ambient temperature range: -20°C to +40°C.

## KLASIFIKACIJA

|                 |                                                    |
|-----------------|----------------------------------------------------|
| Grupė           | Lempos                                             |
| Klasė           | Šviesos diodų lempos                               |
| Pavadinimas     | LED PL Glass TC-S G23 2P 4.5W (9W) 530lm 830 EM+AC |
| Gamintojas      | BAI                                                |
| Serija          | LED PL                                             |
| Tipas           | G23 2P Glass                                       |
| EAN             | 8714681461075                                      |
| Gamintojo kodas | 146107                                             |

## PARAMETRAI

|                          |                            |
|--------------------------|----------------------------|
| Lizdas                   | G23                        |
| Lempos galia [W]         | 4.5 - 4.5                  |
| Nominali įtampa [V]      | 220 - 240                  |
| Įtampos tipas            | AC                         |
| Nominali srovė [mA]      | 36 - 36                    |
| Lempos forma             | Vamzdis su jungtimi 1 gale |
| Spalvinė temperatūra [K] | 3000 - 3000                |

|                                               |                                |
|-----------------------------------------------|--------------------------------|
| Spalva                                        | Balta                          |
| Spalvų atkūrimo koeficientas CRI              | 80-89                          |
| Šviesos srautas [lm]                          | 530 - 530                      |
| Spalvinė temperatūra pagal EN 12464-1         | Šiltai balta mažiau nei 3300 K |
| Lempos efektyvumas [lm/W]                     | 117                            |
| Spinduliavimo kampas [°]                      | 270 - 270                      |
| Diametras [mm]                                | 32                             |
| Ilgis [mm]                                    | 159                            |
| Energetinio efektyvumo klasė                  | E                              |
| Siūlelinio tipo leputės                       | Ne                             |
| Energijos sąnaudos 1000 h [kWh]               | 5                              |
| Vidutinis tarnavimo laikas [h]                | 30000                          |
| Spalvos atitikimas (McAdamo elipsė)           | SDCM6                          |
| Korpuso spalva                                | Balta                          |
| Apsaugos klasė (IP)                           | IP20                           |
| Reguliuojama                                  | Ne                             |
| Paskirtis                                     | Kita                           |
| Minimalus įjungimo ciklų skaičius             | 20000                          |
| Fotobiologinė sauga pagal EN 62471            | RG0                            |
| Galios faktorius                              | 0.5                            |
| Valdymo galimybė                              | Ne                             |
| Stiklo gaubto tipas                           | Baltas                         |
| Su nuotolinio valdymo pulteliu                | Ne                             |
| Galimas IFTTT palaikymas                      | Ne                             |
| Suderinama su Amazon Alexa                    | Ne                             |
| Suderinama su Google Assistant                | Ne                             |
| Suderinama su Apple HomeKit                   | Ne                             |
| Vardinis šviesos srautas pagal IEC 62612 [lm] | 530                            |