



## LED Party Balls Solar Pendant 2M G200 150lm 2500K IP54

*Pakabinamas šviestuvas*

13005

*BAI LED Party Ball Solar Pendant G200 150lm 2500K Opal IP54 Solarpanel 247x140mm 4W 3.7V 2x2000mAh Battery (lithium) Max. length 200cm Incl. Ground spike & mounting accessories*

*With the Bailey Lights LED Party Balls, atmosphere and experience reach a whole new level. The Solar Pendant Party Ball is an elegant, sustainable and versatile hanging lamp that beautifully illuminates terraces, trees and covered outdoor spaces. This lamp operates fully autonomously on solar power, combining stylish design with ease of use. It features a special, replaceable light source powered by a powerful 3.7V / 4W battery. The white opal milky globe emits a warm, soft 2500K light, creating an inviting and cosy ambiance. The globe has a diameter of 20cm. The cable length from the globe to the hanging ring is 50cm, followed by a 150cm cable from the ring to the solar panel. The included solar panel can be mounted in three different ways ground spike, clamp or wall mount with all mounting accessories supplied as standard. Using the included remote control, you can easily adjust the desired light level. After approximately 8 hours of charging in full sunlight, the lamp provides up to 8 hours of atmospheric lighting, depending on the selected setting.*

Pastaba:

- Prieš naudodami perskaitykite instrukciją.

## KLASIFIKACIJA

Grupė	Šviestuvai
Klasė	Pakabinami šviestuvai
Pavadinimas	LED Party Balls Solar Pendant 2M G200 150lm 2500K IP54
Gamintojas	BAI
Serija	LED Party balls
Tipas	
EAN	8714681471203
Gamintojo kodas	147120

## PARAMETRAI

Maksimalus sistemos galingumas [W]	1.5
Nominali įtampa [V]	3.7 - 3.7

Įtampos tipas	DC
Nominali srovė [mA]	400 - 400
Spalvinė temperatūra [K]	2500 - 2500
Šviesos spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviestuvo efektyvumas [lm/W]	100 - 100
Diametras [mm]	200
Lempos tipas	LED keičiama
Jungties tipas	Kita
Apsaugos klasė (IP)	IP54
Reguliuojama	Ne
Atsparumo liepsnai bandymai pagal IEC 60695-2-11	Nenurodyta
Aukštis/gylis [mm]	200
Atsparumas smūgiams	IK05
Lempų lizdai	Kita
Gaubto medžiaga	Baltas plastikas
Pakabuko ilgis [mm]	500 - 2000
Tinka sekančio galingumo lempoms [W]	1.5 - 1.5
Maitinimo šaltinio tipas	Nereikalinga
Su šviesos jutikliu	Taip
Su šviesos šaltiniu	Taip
Su judesio jutikliu	Ne
Galimas IFTTT palaikymas	Ne
Suderinama su Amazon Alexa	Ne
Suderinama su Google Assistant	Ne
Suderinama su Apple HomeKit	Ne
Valdymas per Bluetooth	Ne
Testavimo darbo vietos apšvietimui pagal EN 12464-1	Ne
Su pakaba	Taip
Tinka sekančiam lempų kiekiui	1
Korpuso medžiaga	Plastikas
Korpuso spalva	Baltas
Numatytas eksploatacijos laikas L70/50 prie 25 °C [h]	10000
Elektrosaugos klasė pagal IEC 61140	III
Šviesos šaltinio energijos vartojimo efektyvumo klasė pagal ES reglamentą 2019/2015	Ne
Su buvimo jutikliu	Ne
Sudėtyje yra produktų pagal 2019/2020/ES	Ne
Vardinis šviesos srautas pagal IEC 62722-2-1 [lm]	150 - 150

