



RoBust LED Mini Floodlight 10W 6500K 750lm IP54 5V CLIII

Šviestuvai - prožektorius

13378

BAI RoBust LED Mini Floodlight 10W 6500K 750lm IP54 CLIII
Rechargeable work light 5V/1A 3.7V 1200mAh 67x63x28mm
Black housing with orange rubber 180° rotatable bracket
with magnet and clip Dimming switch
40lm/130lm/460lm/750lm + 0.3M USB-C charging cable

Bailey RoBust mini floodlight - compact size, powerful performance. This powerful mini floodlight is part of the Bailey RoBust LED Charge series and delivers impressive performance in a compact design. Small enough to fit comfortably in your hand, pocket, bag, car glove compartment or clipped to a backpack. The 10W LED produces up to 750 lumens of bright white light (6500K). With four lighting modes, you can adjust the output to suit any situation, achieving up to 12 hours of runtime on the lowest setting. Recharging is quick and easy: using the included USB cable, the light is fully charged within 2 hours. The mini floodlight is 180-degree adjustable, allowing you to position the beam exactly where you need it. It also features a powerful magnet and a clip, making it easy to attach to metal surfaces or hang on hooks and protrusions. Perfect for DIY jobs, camping and outdoor leisure activities.

KLASIFIKACIJA

Grupė	Šviestuvai
Klasė	Šviestuvai - prožektoriai
Pavadinimas	RoBust LED Mini Floodlight 10W 6500K 750lm IP54 5V CLIII
Gamintojas	BAI
Serija	RoBust LED charge
Tipas	
EAN	8714681471098
Gamintojo kodas	147109

PARAMETRAI

Maksimalus sistemos galingumas [W]	10
Nominali įtampa [V]	3.7 - 3.7
Įtampos tipas	DC
Spalvinė temperatūra [K]	6500 - 6500

Šviesos spalva	Balta
Spalvų atkūrimo koeficientas CRI	70-79
Ilgis [mm]	67
Plotis [mm]	28
Lempos tipas	Nekeičiamas LED
Reguliuojamumas	Pasukamas
Aukštis/gylis [mm]	63
Lempų lizdai	Nenurodyta
Šviesos srautas	Tiesioginis
Gaubto medžiaga	Skaidrus plastikas
Tinka sekančio galingumo lempoms [W]	10 - 10
Su šviesos jutikliu	Ne
Su šviesos šaltiniu	Taip
Su judesio jutikliu	Ne
Spinduliavimo kampo reguliavimas	Ne
Šviesos srauto reguliavimas	Montavimo būdu
Tinka sekančiam lempų kiekiui	1
Korpuso medžiaga	Plastikas
Korpuso spalva	Oranžinis
Šviesos pasiskirstymas	Simetriškas
Elektrosaugos klasė pagal IEC 61140	III
Aplinkos temperatūrų diapazonas pagal IEC62722-2-1 [°C]	-10 - 40
Šviesos spalvos reguliavimas	Ne
Šviesos šaltinio energijos vartojimo efektyvumo klasė pagal ES reglan	Nereikalaujama