

## Ignitor ZRM 4.5ES/C for HS 70-400W or HI 35-400W

Starteris šviestuvui

22637



BEE Electronic HID Ignitor ZRM 4.5ES/C 220-240V 50/60Hz for HS 70-400W / HI 35-400W lamps Max 4.6A 4.0-5.1kV

ZRM ES/C standard superimposed-pulse ignitors without a timer are impressively robust and reliable. This product range is characterised by excellent machining quality, premium electronic components and small dimensions. Their application area covers metal halide lamps with wattages from 35 W to 400 W and sodium vapour lamps with wattages from 70W to 400W. Ideally, a superimposed-pulse ignitor is fitted in the fixture/luminaire. The distance to the lamp is limited to 1.5 m max. to ensure reliable lamp starting and also maximum flexibility during maintenance on fixtures/luminaires. Plastic casing with screw terminal connection 1-4 mm<sup>2</sup>, max. casing temperature 105°C. Suitable for luminaires of protection class I and II. ENEC approved.

## KLASIFIKACIJA

Grupė	Apšvietimo valdymas
Klasė	Starteriai šviestuvams
Pavadinimas	Ignitor ZRM 4.5ES/C for HS 70-400W or HI 35-400W
Gamintojas	BAI
Serija	Light control
Tipas	ZRM Ignitor
EAN	8714681402054
Gamintojo kodas	92400040205

## PARAMETRAI

Jungimo tipas	Single
Elektroninis	Taip
Tinka kompaktinės liuminescencinėms lempoms	Ne
Tinka liuminescencinėms lempoms	Ne
Tinka gyvsidabrio garų lempoms	Taip
Tinka aukšto slėgio natrio garų lempoms	Taip
Tinka sekancio galingumo lempoms [W]	35 - 400

