

EcoPack 5pcs LED FIL Safe G45 E27 2W 2700K PC CL

LED lempa

34083



BAI EcoPack 5pcs LED Filament Safe Ball G45 E27 2W 2700K Clear 160lm (16W) 230V-240V 360D 45x70mm IP44 Shatterproof Polycarbonate LED-lamp

The LED filament Safe series responds to the desire to also use the decorative filament bulbs where shards are extremely undesirable when broken. Think of professional (open) kitchens, above tables in a restaurant, above the food department in and on the market. The bulb is made of polycarbonate which is much stronger than the traditional glass shade and also does not splinter. This also makes the lamp ideal for use in barbed cables at (temporary) festivals or events. When mounted hanging in combination with a suitable lamp holder (holder makes a watertight seal with the bulb) also outdoors applicable. We advise to use this lamp in combination with the Bailey Light Strings of 5, 10, 25 or 50m. The party bulbs are standard in an environmentally friendly EcoPack packaging of 5 pieces, which means less waste and handling. Moreover, this lamp is durable and energy efficient.

KLASIFIKACIJA

Grupė	Lempos
Klasė	Šviesos diodų lempos
Pavadinimas	EcoPack 5pcs LED FIL Safe G45 E27 2W 2700K PC CL
Gamintojas	BAI
Serija	LED Filament safe
Tipas	G45 EcoPack
EAN	8714681440827
Gamintojo kodas	144082

PARAMETRAI

Lizdas	E27
Lempos galia [W]	2 - 2
Nominali įtampa [V]	220 - 240
Įtampos tipas	AC

Nominali srovė [mA]	15 - 15
Lempos forma	Rutulys
Spalvinė temperatūra [K]	2700 - 2700
Šviesos spalva	827 - 827
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	160 - 160
Lempos efektyvumas [lm/W]	80
Spinduliavimo kampas [°]	360
Diametras [mm]	45
Ilgis [mm]	70
Energetinio efektyvumo klasė	A++
Energetinio efektyvumo indeksas (EEI)	0.11
Energijos sąnaudos 1000 h [kWh]	2
Spalvinė temperatūra pagal EN 12464-1	Šiltai balta mažiau nei 3300 K
Siūlelinio tipo leputės	Taip
Vidutinis tarnavimo laikas [h]	15000
Spalvos atitikimas (McAdamo elipsė)	SDCM6
Korpuso spalva	Skaidri
Apsaugos klasė (IP)	IP20
Reguliuojama	Ne
Paskirtis	Kita
Minimalus įjungimo ciklų skaičius	7500
Fotobiologinė sauga pagal EN 62471	Kita
Galios faktorius	0.5
Valdymo galimybė	Ne
Stiklo gaubto tipas	Skaidri
Su nuotolinio valdymo pulteliu	Ne