



LUMILUX© XT T8 58 W/840 XT

Liuminescencinė lempa

41750

Tubular fluorescent lamps 26mm, with G13 bases, long life. CBP_01.00 Product features, all [calc.]: Extremely reliable: long life, low premature failure rate, 90 % luminous flux throughout their life. Service life: up to 42,000 h on preheat ECGs or up to 35,000 h on CCGs. Good color rendering group: 1B (Ra: 80-89). Dimmable (for details see the Technical Guide). Top-quality three-band phosphor: LUMILUX©. CBP_02.00 Product benefits, all [calc.]: Much lower total cost of ownership (TCO) compared with T8 LUMILUX© lamps. Service life 2.3 times higher than that of a standard LUMILUX© lamp. Longer standard lifetime, so fewer lamps for waste disposal. CBP_03.00 Areas of applicat, all [calc.]: Installations where relamping would disturb normal operations. Street lighting. Public buildings. Industry. Shops. Supermarkets and department stores.

KLASIFIKACIJA

Grupė	Lempos
Klasė	Liuminescencinės lempos
Pavadinimas	LUMILUX© XT T8 58 W/840 XT
Gamintojas	OSRAM
Serija	7CC 30 50
Tipas	L 58W/840 XT FLH1
EAN	4008321209320
Gamintojo kodas	4008321209320

PARAMETRAI

Lizdas	G13
Lempos galia [W]	58
Lempos forma	Strypas
Spalvinė temperatūra [K]	4000
Šviesos spalva	840
Spalva	Balta
Spalvų atkūrimo koeficientas CRI	80-89
Šviesos srautas [lm]	5200
Lempos efektyvumas [lm/W]	90

Vamzdžio diametras [mm]	26
Ilgis [mm]	1500
Energetinio efektyvumo klasė	A
Energijos sąnaudos 1000 h [kWh]	68
Spalvinė temperatūra pagal EN 12464-1	Neutrali balta 3300-5300K
Išorinė uždegimo juosta	Ne
Pritaikymas	Bendram naudojimui
Vidutinis tarnavimo laikas [h]	55000
Pilno spektro lempa	Ne
Paskirtis	T2
Žiedo diametras [mm]	26
Su cokolių apsauga	Ne
Naudojama be starterio	Ne
Tinka avariniam apšvietimui	Ne
Tinka sprogios aplinkos šviestuvams	Ne