



Spiraled Nostalgic ST64 E27 4W 2200K Clear Dimm

LED lempa

77426

BAI Spiraled Nostalgic ST64 E27 4W 2200K Clear 170lm (18W) Dimmable CRI90 230V-240V 360D 64x140mm LED Filament lamp

In 2016, Bailey revolutionized the LED light source industry with an LED version of the original carbon filament bulb. The Spiraled lamps are proof that the atmosphere and appearance of this beloved lamp can be perfectly imitated. The curled LED filaments ensure that the LED light bulb, in addition to light, brings a lot of atmosphere. Over the years, the series has been expanded and it is one of the most successful series of decorative LED lamps in the professional market. Spiraled lamps last much longer than incandescent and halogen lamps and use less energy. In addition, these lamps are dimmable on an approved LED dimmer. Spiraled is a protected brand name.

KLASIFIKACIJA

| | |
|-----------------|-------------------------------------------------|
| Grupė | Lempos |
| Klasė | Šviesos diodų lempos |
| Pavadinimas | Spiraled Nostalgic ST64 E27 4W 2200K Clear Dimm |
| Gamintojas | BAI |
| Serija | Spiraled Nostalgic |
| Tipas | ST64 |
| EAN | 8714681430330 |
| Gamintojo kodas | 143033 |

PARAMETRAI

| | |
|--------------------------|----------------------------|
| Lizdas | E27 |
| Lempos galia [W] | 4 - 4 |
| Nominali įtampa [V] | 220 - 240 |
| Įtampos tipas | AC |
| Nominali srovė [mA] | 17 - 17 |
| Lempos forma | Vamzdis su jungtimi 1 gale |
| Spalvinė temperatūra [K] | 2200 - 2200 |

| | |
|---------------------------------------|--------------------------------|
| Šviesos spalva | 922 - 922 |
| Spalva | Balta |
| Spalvų atkūrimo koeficientas CRI | 90-100 |
| Šviesos srautas [lm] | 170 - 170 |
| Lempos efektyvumas [lm/W] | 42 |
| Spinduliavimo kampas [°] | 360 |
| Diametras [mm] | 64 |
| Ilgis [mm] | 140 |
| Energetinio efektyvumo klasė | A |
| Energetinio efektyvumo indeksas (EEI) | 0.2 |
| Energijos sąnaudos 1000 h [kWh] | 4 |
| Spalvinė temperatūra pagal EN 12464-1 | Šiltai balta mažiau nei 3300 K |
| Siūlelinio tipo leputės | Taip |
| Vidutinis tarnavimo laikas [h] | 20000 |
| Spalvos atitikimas (McAdamo elipsė) | SDCM6 |
| Korpuso spalva | Skaidri |
| Apsaugos klasė (IP) | IP20 |
| Reguliuojama | Taip |
| Paskirtis | Kita |
| Minimalus įjungimo ciklų skaičius | 10000 |
| Fotobiologinė sauga pagal EN 62471 | Kita |
| Galios faktorius | 0.85 |
| Valdymo galimybė | Ne |
| Stiklo gaubto tipas | Skaidri |
| Su nuotolinio valdymo pulteliu | Ne |