



PAR56

PAR56 300W GX16d 230V FL 1CT/6

Extremely powerful pressed-glass 179 mm diameter reflector lamps

Product data


General Information	
Cap-Base	GX16D [GX16d]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	-
Gas Filling	Gas
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X
Light Technical	
Beam Angle (Nom)	25 °
Luminous Flux (Rated) (Nom)	2337 lm
Luminous Intensity (Max)	22000 cd
Beam Description	Flood
Rated Beam Angle	25 °
Correlated Color Temperature (Nom)	2700 K
Color Rendering Index (Nom)	100
Luminous Flux in 90° Cone (Rated)	2337 lm
Operating and Electrical	
Power (Rated) (Nom)	300.0 W
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light

Voltage (Nom)	230 V
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label (EEL)	D
Energy Consumption kWh/1000 h	300 kWh

Product Data	
Full product code	871150015961810
Order product name	PAR56 300W GX16d 230V FL 1CT/6
EAN/UPC - Product	8711500159618
Order code	923804144221
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	923804144221
Net Weight (Piece)	504.000 g
ILCOS Code	IPAR-300-230-GX16d-179/25/11

PAR56

Dimensional drawing



Product	D (max)	C (max)	C1
PAR56 300W GX16d 230V FL 1CT/6	178.5 mm	126.9 mm	98 mm

PAR56 300W GX16d 230V FL

