



MASTERColour CDM-TC

MASTERColour CDM-TC 35W/842 G8.5 1CT/12

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

Product data

General Information	
Cap base	G8.5 [G8.5]
Operating position	UNIVERSAL [Any/Universal]
Life to 5% failures (nom.)	6000 h
Life to 10% failures (nom.)	8000 h
Life to 20% failures (nom.)	9000 h
Life to 50% failures (nom.)	12000 h
ANSI code HID	-
Light Technical	
Colour code	842 [CCT of 4,200 K]
Luminous flux (rated) (nom.)	3100 lm
Colour designation	Cool White (CW)
Lumen maintenance 10,000 hours (nom.)	70 %
Lumen maintenance 2,000 hours (min.)	75 %
Lumen maintenance 2,000 hours (nom.)	85 %
Lumen maintenance 5,000 hours (min.)	70 %
Lumen maintenance 5,000 hours (nom.)	80 %
Chromaticity coordinate X (nom.)	0.374
Chromaticity coordinate Y (nom.)	0.369
Correlated colour temperature (nom.)	4200 K
Luminous efficacy (rated) (nom.)	79 lm/W

Color rendering index (nom.)	85
Operating and Electrical	
Power (Rated) (Min)	39.0 W
Power (Rated) (Nom)	39.0 W
Ignition supply voltage (max.)	198 V
Ignition supply voltage (min.)	198 V
Re-ignition time (min.) (max.)	15 min
Ignition time (max.)	30 s
Voltage (Max)	93 V
Voltage (Min)	77 V
Voltage (Nom)	85 V
Controls and Dimming	
Dimmable	no
Run-up time 90% (max.)	3 min
Mechanical and Housing	
Bulb finish	Clear
Bulb material	UV-Block Quartz

MASTERColour CDM-TC

Approval and Application	Approval	and	Application	
--------------------------	----------	-----	-------------	--

Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	2.7 mg
Energy Consumption kWh/1000 h	43 kWh
UV	
PET (NIOSH) (min.)	8 h/500lx
Damage factor D/fc (max.)	0.5
Luminaire Design Requirements	
Bulb temperature (max.)	500 °C
Pinch temperature (max.)	300 °C


871150020957315

Order product name	MASTERColour CDM-TC 35W/842 G8.5
	1CT/12
EAN/UPC – product	8711500209573
Order code	20957315
Local Code	35CDMTC942
Numerator – quantity per pack	1
Numerator – packs per outer box	12
Material no. (12NC)	928093805125
Net weight (piece)	10.000 g
ILCOS Code	MT/UB-35/842-H-G8.5-17/85

Warnings and Safety

Product Data Full product code

Dimensional drawing



Photometric data




Product

MASTERColour CDM-TC 35W/842 G8.5 1CT/12

MASTERColour CDM-TC

Lifetime



LDLE_CDM-TC_0001-Life expectancy diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2020, March 19 - data subject to change