



MASTER PL-S 4 Pin

MASTER PL-S 9W/830/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 2 parallel narrow fluorescent tubes

Product data

General Information	
Cap base	2G7 [2G7]
Life to 50% failures preheat (nom.)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	92 %
LSF Preheat 16000 h Rated	30 %
Light Technical	
Colour code	830 [CCT of 3,000 K]
Luminous flux (nom.)	600 lm
Luminous flux (rated) (nom.)	583 lm
Colour designation	Warm white (WW)
Correlated colour temperature (nom.)	3000 K
Luminous efficacy (rated) (nom.)	73 lm/W
Color rendering index (nom.)	82
LLMF 2000 h Rated	95 %
LLMF 4000 h Rated	92 %
LLMF 6000 h Rated	90 %
LLMF 8000 h Rated	88 %
LLMF 12000 h Rated	86 %
Operating and Electrical	
Power (Rated) (Nom)	8.6 W


Lamp current (nom.)	0.170 A
Temperature	
Design temperature (nom.)	28 °C
Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Cap base information	4P
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	9 kWh
Product Data	
Full product code	871150026093270
Order product name	MASTER PL-S 9W/830/4P 1CT/5X10BOX
EAN/UPC – product	8711500260932
Order code	26093270
Local Code	PLS98304P
Numerator – quantity per pack	1
Numerator – packs per outer box	50
Material no. (12NC)	927936283011

MASTER PL-S 4 Pin

Net weight (piece)	30.000 g
ILCOS Code	FSD-9/30/1B-E-2G7

Warnings and Safety


Dimensional drawing




PL-S 9W/830/4P LM

Product	MASTER PL-S 9W/830/4P 1CT/5X10BOX
---------	-----------------------------------

Photometric data




Lightcolour /830




Lightcolour /830

Lifetime



LDLE_PLS4PLM_0001-Life expectancy diagram



MASTER PL-S 4 Pin

Lifetime

