



# MASTER TL-E Circular Super 80

## TL-E 40W/830 1CT/12

Low-pressure mercury discharge lamps with a circular 26 mm tube

### Product data

General Information	
Cap-Base	G10Q [ G10q]
Life to 50% Failures (Nom)	13000 h
LSF 2000 h Rated	98 %
LSF 4000 h Rated	77 %
LSF 6000 h Rated	60 %
LSF 8000 h Rated	45 %

Light Technical	
Colour Code	830 [ CCT of 3000K]
Luminous Flux (Nom)	3200 lm
Luminous Flux (Rated) (Nom)	3200 lm
Colour Designation	Warm White (WW)
Colour Temperature, horizontal (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Colour Rendering Index horiz (Nom)	80
Depreciation 2000 hrs	89 %
LLMF 4000 h Rated	84 %
Depreciation 5000 hrs	81 %
LLMF 8000 h Rated	80 %

Operating and Electrical	
Power (Rated) (Nom)	40.0 W

Lamp Current (Nom)	0.420 A
Voltage (Nom)	110 V

Temperature	
Design Temperature (Nom)	25 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Efficiency Label	A
Mercury (Hg) Content (Nom)	8 mg
Energy Consumption kWh/1000 h	44 kWh

Product Data	
Full product code	871150028476115
Order product name	TL-E 40W/830 1CT/12
EAN/UPC - Product	8711500284761
Order code	28476115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928027483070
Net Weight (Piece)	0.250 kg


# MASTER TL-E Circular Super 80

ILCOS Code

FSC-40/30/1B-E-G10q-29/400

## Warnings and Safety

### Dimensional drawing




TL-E 40W/830

### Product

TL-E 40W/830 1CT/12

### Photometric data



Lightcolour /830

Lightcolour /830

