



# Halogen non-reflector

## 6550 150W G6.35 15V 1CT/10X10F

Low-voltage quartz halogen capsule lamps

#### **Product data**


General Information					
Cap base	G6.35 [ G6.35]				
Philips code	6550				
ANSI Code	EVB-BRJ				
LIF code	A1/234				
Operating position	S90 [ Standing +/-90D or Base Down (BDH)]				
Main application	Projection				
Life to 50% failures (nom.)	50 h				
Light Technical					
Luminous flux (rated) (nom.)	5600 lm				
Correlated colour temperature (nom.)	3450 K				
Color rendering index (nom.)	100				
Operating and Electrical					
Power (Rated) (Nom)	150 W				
Voltage (Nom)	15 V				
Mechanical and Housing					
Bulb material	Quartz-UV Open				

Filament shape	Flat				
Filament dimensions WxH	4.8x3.0				
Luminaire Design Requirements					
Bulb temperature (max.)	900 ℃				
Pinch temperature (max.)	400 °C				
Product Data					
Full product code	871150040984350				
Order product name	6550 150W G6.35 15V 1CT/10X10F				
EAN/UPC - product	8711500409843				
Order code	40984350				
Local Code	A1234				
Numerator – quantity per pack	1				
Numerator – packs per outer box	100				
Material no. (12NC)	923870618503				
Net weight (piece)	0.002 kg				

Datasheet, 2018, December 28 data subject to change

### Halogen non-reflector

#### Dimensional drawing



6550 150W G6.35 15V

Product	D (max)	L (min)	L (max)	L	P (max)	Р	P (min)	C (max)
6550 150W	11.5 mm	29.75	30.25	30	1.05 mm	1 mm	0.95	44 mm
G6.35 15V		mm	mm	mm			mm	
1CT/10X10F								

