



Halogen non-reflector

7748XHP 250W G6.35 24V 1CT/10X10F

Low-voltage quartz halogen capsule lamps

Product data

| General Information | |
|-----------------------------|---|
| Cap base | G6.35 [G6.35] |
| Philips code | 7748XHP |
| ANSI Code | EHJ |
| LIF code | A1/223 |
| Operating position | S90 [Standing +/-90D or Base Down (BDH)] |
| Main application | Projection |
| Life to 50% failures (nom.) | 50 h |

| Light Technical | |
|--------------------------------------|----------|
| Luminous flux (rated) (nom.) | 10000 lm |
| Correlated colour temperature (nom.) | 3550 K |
| Color rendering index (nom.) | 100 |

| Operating and Electrical | |
|--------------------------|-------|
| Power (Rated) (Nom) | 250 W |
| Voltage (Nom) | 24 V |

| Mechanical and Housing | |
|------------------------|----------------|
| Bulb material | Quartz-UV Open |

| | |
|-------------------------|---------|
| Filament shape | Flat |
| Filament dimensions WxH | 7.0x3.5 |

| Luminaire Design Requirements | |
|-------------------------------|--------|
| Bulb temperature (max.) | 900 °C |
| Pinch temperature (max.) | 400 °C |

| Product Data | |
|---------------------------------|-----------------------------------|
| Full product code | 871150041029050 |
| Order product name | 7748XHP 250W G6.35 24V 1CT/10X10F |
| EAN/UPC – product | 8711500410290 |
| Order code | 41029050 |
| Local Code | A1223X |
| Numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 100 |
| Material no. (12NC) | 924006520503 |
| Net weight (piece) | 0.004 kg |

Halogen non-reflector

Dimensional drawing



Product

7748XHP 250W G6.35 24V 1CT/10X10F

7748XHP 250W G6.35 24V

