



# Halogen Low Voltage

## 14515 FO 75W GX5.3 12V 1CT/10X5F

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.

### Product data

General Information	
Cap-Base	GX5.3 [ GX5.3]
Philips Code	14515 FO
ANSI Code	-
LIF Code	-
Operating Position	S90 [ Standing +/-90D or Base Down (BDH)]
Main Application	Projection
Life to 50% Failures (Nom)	1600 h
J Code	-
Light Technical	
Luminous Flux (Rated) (Nom)	420 lm
Correlated Color Temperature (Nom)	2900 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	75 W
Voltage (Nom)	12 V


Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	-
Bulb Material	Quartz-UV Open
Reflector Finish	-
Filament Shape	-
Filament Dimensions WxH	-
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C
Working Distance WD	30 mm
Product Data	
Full product code	871150041099360
Order product name	14515 FO 75W GX5.3 12V 1CT/10X5F
EAN/UPC - Product	8711500410993

Halogen Low Voltage

Order code	924034417104
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924034417104

Net Weight (Piece)	0.025 kg
--------------------	----------

Dimensional drawing



14515 FO 75W GX5.3 12V

Product	D (max)	C (max)
14515 FO 75W GX5.3 12V 1CT/10X5F	50 mm	42 mm

