



Accentline

Accentline 50W GU5.3 12V 36D 1CT/10X5F

Low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.

Product data

General Information	
Cap-Base	GU5.3 [GU5.3]
Philips Code	14600
Operating Position	UNIVERSAL [Any or Universal (U)]
ANSI Code Halogen	EXN
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X
Light Technical	
Beam Angle (Nom)	36 °
Luminous Intensity (Max)	1200 cd
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	50 W
Lamp Current (Nom)	4.17 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Efficiency Label (EEL)	B
Energy Consumption kWh/1000 h	53 kWh
Luminaire Design Requirements	
Cap-Base Temperature (Max)	250 °C
Product Data	
Full product code	871150041205800
Order product name	Accentline 50W GU5.3 12V 36D 1CT/10X5F
EAN/UPC - Product	8711500412058
Order code	926000850034
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	926000850034
Net Weight (Piece)	0.032 kg
ILCOS Code	HRGI-50-12-GU5.3-50/36

Accentline

Dimensional drawing



Product	D (max)	C (max)
Accentline 50W GU5.3 12V 36D 1CT/10X5F	51 mm	46 mm

Fighter 14600 50W GU5.3 12V MR16 36D

Photometric data

