



Capsuleline

Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

Product data


General Information	
Cap-Base	GY6.35 [GY6.35]
Philips Code	14730
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X
Light Technical	
Luminous Flux (Nom)	850 lm
Luminous Flux (Rated) (Nom)	850 lm
Correlated Color Temperature (Nom)	2900 K
Luminous Efficacy (rated) (Nom)	17 lm/W
Color Rendering Index (Nom)	100
LLMF at End of Nominal Lifetime (Min)	80 %
Operating and Electrical	
Power (Rated) (Nom)	50.0 W
Lamp Current (Nom)	4.17 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	-
Approval and Application	
Energy Efficiency Label (EEL)	C
Energy Consumption kWh/1000 h	53 kWh
Luminaire Design Requirements	
Bulb Temperature (Max)	250 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	871150041295950
Order product name	Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F
EAN/UPC - Product	8711500412959
Order code	924892217108
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100

Capsuleline

Material Nr. (12NC)	924892217108
Net Weight (Piece)	0.002 kg
ILCOS Code	HSG/C/UB-50-12-GY6.35

Dimensional drawing



CAP Fighter 14730 50W GY6.35 12V CL

Product	D (max)	L	C (max)
Capsuleline 50W GY6.35 12V CL 2000h 1CT/ 10X10F	12 mm	30 mm	44 mm

