



Capsuleline

Capsuleline 10W G4 12V CL 2000h 1CT/10X10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact Capsuleline delivers crisp white light over a long lifetime.

Product data

General Information	
Cap-Base	G4 [G4]
Philips Code	18182
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X

Light Technical	
Luminous Flux (Nom)	100 lm
Luminous Flux (Rated) (Nom)	100 lm
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	10 lm/W
Color Rendering Index (Nom)	100
LLMF at End of Nominal Lifetime (Min)	80 %

Operating and Electrical	
Power (Rated) (Nom)	10.0 W
Lamp Current (Nom)	0.83 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	instant full light
Power Factor (Nom)	1
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	-

Approval and Application	
Energy Efficiency Label (EEL)	C
Energy Consumption kWh/1000 h	11 kWh

Luminaire Design Requirements	
Bulb Temperature (Max)	220 °C
Pinch Temperature (Max)	350 °C


Product Data	
Full product code	871150041298050
Order product name	Capsuleline 10W G4 12V CL 2000h 1CT/10X10F
EAN/UPC - Product	8711500412980
Order code	924891917110
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	924891917110
Net Weight (Piece)	0.002 kg

Capsuleline

ILCOS Code

HSG/C/UB-10-12-G4

Dimensional drawing



Product	D (max)	L	C (max)
Capsuleline 10W G4 12V CL 2000h 1CT/10X10F	10 mm	22.2 mm	33 mm

CAP Fighter 18182 10W G4 12V CL

