



Brilliantline Alu

Brilliantline Alu 20W GU5.3 12V MR16 36D 1CT/10X5F

Superior-quality low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Aluminum coating prevents heat in the backlight.

Product data

General Information		Power Factor (Nom)	
Cap-Base	GU5.3 [GU5.3]		1
Philips Code	14715	Voltage (Nom)	12 V
Operating Position	UNIVERSAL [Any or Universal (U)]	Controls and Dimming	
ANSI Code Halogen	BAB	Dimmable	Yes
Nominal Lifetime (Nom)	4000 h	Mechanical and Housing	
Switching Cycle	16000X	Bulb Finish	Clear
Light Technical		Approval and Application	
Beam Angle (Nom)	36 °	Energy Efficiency Label (EEL)	B
Luminous Flux (Rated) (Nom)	230 lm	Energy Consumption kWh/1000 h	21 kWh
Luminous Intensity (Max)	700 cd	Luminaire Design Requirements	
Rated Beam Angle	36 °	Bulb Temperature (Max)	250 °C
Correlated Color Temperature (Nom)	3000 K	Cap-Base Temperature (Max)	350 °C
Color Rendering Index (Nom)	100	Product Data	
LLMF at End of Nominal Lifetime (Min)	80 %	Full product code	871150043072460
Luminous Flux in 90° Cone (Rated)	230 lm	Order product name	Brilliantline Alu 20W GU5.3 12V MR16 36D 1CT/10X5F
Operating and Electrical		EAN/UPC - Product	8711500430724
Power (Rated) (Nom)	20.0 W	Order code	924057217101
Lamp Current (Nom)	1.72 A		
Starting Time (Nom)	0.0 s		
Warm Up Time to 60% Light (Nom)	instant full light		

Brilliantline Alu


Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924057217101
Net Weight (Piece)	30.000 g

ILCOS Code	HAGS-20-12-GU5.3-50/36
------------	------------------------

Warnings and Safety

- Due to the heat that radiates from the bulb, a minimum distance of 0,5 m is required between bulb and combustible materials or objects susceptible to drying or fading.



Dimensional drawing



ALU 14715 20W GU5.3 12V MR16 36D

Product	D (max)	C (max)
Brilliantline Alu 20W GU5.3 12V MR16 36D 1CT/10X5F	51 mm	46 mm

Photometric data



Brilliantline Alu 20W 36D

