



# MASTER PL-T TOP 4 Pin

# MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX

MASTER PL-T TOP is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The Philips amalgam technology guarantees optimum performance in applications with a wide temperature range, enabling significantly higher output and efficacy levels. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

### **Product data**

General Information	
Cap-Base	GX24Q-3 [ GX24q-3]
Life to 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light Technical	
Color Code	840 [ CCT of 4000K]
Luminous Flux (Nom)	2400 lm
Luminous Flux (Rated) (Nom)	2400 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (Rated) (Min)	75 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	85 %

LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %
Operating and Electrical	
Power (Nom)	32.0 W
Lamp Current (Nom)	0.320 A
Temperature	
Design Temperature (Nom)	28 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	4 Pins
Approval and Application	
Energy Efficiency Label (EEL)	А
Mercury (Hg) Content (Nom)	1.4 mg

Datasheet, 2020, March 24 data subject to change


# **MASTER PL-T TOP 4 Pin**

Energy Consumption kWh/1000 h	36 kWh
Product Data	
Full product code	871150056026170
Order product name	MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX
EAN/UPC - Product	8711500560261
Order code	927911984069

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927911984069
Net Weight (Piece)	70.000 g
ILCOS Code	FSMH-32/40/1B-L/P-GX24q=3

# Warnings and Safety

### Dimensional drawing




PL-T TOP 32W/840/4P A


### Product

MASTER PL-T TOP 32W/840/4P 1CT/5X10BOX

### Photometric data










# **MASTER PL-T TOP 4 Pin**


### Lifetime





LDLM\_PLTTOP4P\_0001-Lumen maintenance diagram





LDLE\_PLTTOP4P\_0002-Life expectancy diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.