



MASTER SOX PSG

MASTER SOX PSG 35W BY22D T50 SLV/12

Low-pressure sodium vapour lamps with a U-shaped discharge tube enclosed in a clear tubular outer bulb under vacuum that is maintained by a solid-state getter


Product data

General Information	
Cap base	BY22D [BY22d]
Operating position	H110 [Hanging +/-110D or Base Up (BU)]
Life to 10% failures (nom.)	12000 h
Life to 50% failures (nom.)	18000 h
Light Technical	
Luminous flux (rated) (min.)	4250 lm
Luminous flux (rated) (nom.)	4700 lm
Lumen maintenance 10,000 hours (nom.)	95 %
Lumen maintenance 2,000 hours (nom.)	95 %
Lumen maintenance 5,000 hours (nom.)	95 %
Correlated colour temperature (nom.)	1800 K
Luminous efficacy (rated) (nom.)	127 lm/W
Operating and Electrical	
Lamp current (nom.)	0.53 A
Ignition peak voltage (max.)	390 V
Ignition time (max.)	10 s
Voltage (Nom)	70 V
Controls and Dimming	
Dimmable	no

Mechanical and Housing	
Bulb finish	Clear (CL)
Approval and Application	
Energy efficiency label (EEL)	A+
Mercury (Hg) content (nom.)	0 mg
Energy Consumption kWh/1000 h	41 kWh
Luminaire Design Requirements	
Bulb temperature (max.)	150 °C
Cap base temperature (max.)	150 °C
Product Data	
Full product code	871150059976615
Order product name	MASTER SOX PSG 35W BY22d T50 1SL/12
EAN/UPC – product	8711500599766
Order code	59976615
Local Code	35SOXPSG
Numerator – quantity per pack	1
Numerator – packs per outer box	12
Material no. (12NC)	928148100058
Net weight (piece)	0.217 kg

MASTER SOX PSG

Dimensional drawing



Product	D (max)	C (max)
MASTER SOX PSG 35W BY22d T50 1SL/12	52 mm	311 mm

SOX PSG 35W BY22d T50

Lifetime

