



# MASTER PL-T 4 Pin

## MASTER PL-T 42W/830/4P 1CT/5X10CC

Energy saving compact fluorescent lamp Compact long-arc low-pressure mercury discharge lamp Envelope consists of 6 parallel narrow fluorescent tubes

### Product data

General Information	
Cap base	GX24Q-4 [ GX24q-4]
Life to 50% failures preheat (nom.)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light Technical	
Colour code	830 [ CCT of 3,000 K]
Luminous flux (nom.)	3200 lm
Luminous flux (rated) (nom.)	3050 lm
Colour designation	Warm white (WW)
Correlated colour temperature (nom.)	3000 K
Luminous efficacy (rated) (min.)	74 lm/W
Color rendering index (nom.)	>80
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	86 %
LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	41.0 W


Lamp current (nom.)	0.320 A
Temperature	
Design temperature (nom.)	28 °C
Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Cap base information	4P
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	45 kWh
Product Data	
Full product code	871150061134570
Order product name	MASTER PL-T 42W/830/4P 1CT/5X10BOX
EAN/UPC – product	8711500611345
Order code	61134570
Local Code	42PLT8304PINCS
Numerator – quantity per pack	1
Numerator – packs per outer box	50
Material no. (I2NC)	927914883071

# MASTER PL-T 4 Pin

Net weight (piece)	83.000 g
ILCOS Code	FSMH-42/30/1B-L/P-GX24q=4

## Warnings and Safety


## Dimensional drawing




PL-T 42W/830/4P M

Product	MASTER PL-T 42W/830/4P 1CT/5X10BOX
---------	------------------------------------

## Photometric data




Lightcolour /830



Lightcolour /830

## Lifetime



LDLE\_PLT4PN\_0002-Life expectancy diagram

# MASTER PL-T 4 Pin

## Lifetime



LDLM\_PLT4PN\_0001-Lumen maintenance diagram

