



MASTER PL-C 2 Pin

MASTER PL-C 18W/840/2P 1CT/5X10BOX

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

Product data

General Information					
Cap base	G24D-2 [G24d-2]				
Life to 10% failures (nom.)	6500 h				
Life to 50% failures (nom.)	10000 h				
LSF 2000 h Rated	99 %				
LSF 4000 h Rated	98 %				
LSF 6000 h Rated	92 %				
LSF 8000 h Rated	78 %				
Light Technical					
Colour code	840 [CCT of 4,000 K]				
Luminous flux (nom.)	1200 lm				
Luminous flux (rated) (nom.)	1200 lm				
Colour designation	Cool White (CW)				
Correlated colour temperature (nom.)	4000 K				
Luminous efficacy (rated) (nom.)	67 lm/W				
Color rendering index (nom.)	82				
LLMF 2000 h Rated	92 %				
LLMF 4000 h Rated	87 %				
LLMF 6000 h Rated	83 %				
LLMF 8000 h Rated	81 %				
Operating and Electrical					
Power (Rated) (Nom) 17.9 W					

Lamp current (nom.)	0.230 A				
Temperature					
Design temperature (nom.)	28 °C				
Controls and Dimming					
Dimmable	no				
Mechanical and Housing					
Cap base information	2P				
Approval and Application					
Energy efficiency label (EEL)	В				
Mercury (Hg) content (nom.)	1.4 mg				
Energy Consumption kWh/1000 h	22 kWh				
Product Data					
Full product code	871150062093470				
Order product name	MASTER PL-C 18W/840/2P 1CT/5X10BOX				
EAN/UPC – product	8711500620934				
Order code	62093470				
Numerator – quantity per pack	1				
Numerator – packs per outer box	50				
Material no. (12NC)	927905784040				
Net weight (piece)	57.800 g				


MASTER PL-C 2 Pin

ILCOS Code

FSQ-18/40/1B-I-G24d=2

Warnings and Safety


Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 18W/840/2P	27.1 mm	27.1 mm	109.5 mm	128.0 mm	150.4 mm
1CT/5X10BOX					

PL-C 18W/840/2P


Photometric data





Lightcolour /840

Lifetime




LDLE_PLC2P_0001-Life expectancy diagram

Lightcolour /840

500

MASTER PL-C 2 Pin

Lifetime



LDLM_PLC2P_0001-Lumen maintenance diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2020, March 19 - data subject to change