



MASTER PL-C 4 Pin

MASTER PL-C 18W/827/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 4 parallel narrow fluorescent tubes

Product data


General Information	
Cap-Base	G24Q-2 [G24q-2]
Life to 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light Technical	
Colour Code	827 [CCT of 2700K]
Luminous Flux (Nom)	1200 lm
Luminous Flux (Rated) (Nom)	1200 lm
Colour Designation	Incandescent White
Colour Temperature, horizontal (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	67 lm/W
Colour Rendering Index horiz (Nom)	82
Depreciation 2000 hrs	92 %
LLMF 4000 h Rated	87 %
Depreciation 5000 hrs	83 %
LLMF 8000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	16.5 W
Lamp Current (Nom)	0.230 A

Temperature	
Design Temperature (Nom)	28 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	4P
Approval and Application	
Energy Efficiency Label	A
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	20 kWh
Product Data	
Full product code	871150062327070
Order product name	MASTER PL-C 18W/827/4P 1CT/5X10BOX
EAN/UPC - Product	8711500623270
Order code	62327070
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927907282740
Net Weight (Piece)	55.300 g
ILCOS Code	FSQ-18/27/1B-E-G24q=2

MASTER PL-C 4 Pin

Warnings and Safety

Dimensional drawing




PL-C 18W/827/4P


Product

MASTER PL-C 18W/827/4P 1CT/5X10BOX

Photometric data





Lightcolour /827



Lightcolour /827

Lifetime



LDLE_PLC4P_0002-Life expectancy diagram

MASTER PL-C 4 Pin

Lifetime

