



# MASTER PL-C 4 Pin

## MASTER PL-C 10W/840/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 4 parallel narrow fluorescent tubes

### Product data


General Information	
Cap base	G24Q-1 [ G24q-1]
Life to 50% failures preheat (nom.)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %
Light Technical	
Colour code	840 [ CCT of 4,000 K]
Luminous flux (nom.)	600 lm
Luminous flux (rated) (nom.)	600 lm
Colour designation	Cool White (CW)
Correlated colour temperature (nom.)	4000 K
Luminous efficacy (rated) (nom.)	60 lm/W
Color rendering index (nom.)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	10.0 W
Lamp current (nom.)	0.190 A

Temperature	
Design temperature (nom.)	28 °C
Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Cap base information	4P
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	11 kWh
Product Data	
Full product code	871150062330070
Order product name	MASTER PL-C 10W/840/4P 1CT/5X10BOX
EAN/UPC – product	8711500623300
Order code	62330070
Local Code	10PLC8404PIN
Numerator – quantity per pack	1
Numerator – packs per outer box	50
Material no. (12NC)	927907084040
Net weight (piece)	41.400 g
ILCOS Code	FSQ-10/40/1B-E-G24q=1

# MASTER PL-C 4 Pin

## Warnings and Safety


## Dimensional drawing




PL-C 10W/840/4P

**Product**  
MASTER PL-C 10W/840/4P 1CT/5X10BOX

## Photometric data





Lightcolour /840



Lightcolour /840

## Lifetime



LDLE\_PLC4P\_0002-Life expectancy diagram

# MASTER PL-C 4 Pin

## Lifetime

