



Softone Globe

Softone Globe 16W WW E27 G120 1CH/4

Decorative covered energy-saving lamps in Globe shape, for consumer applications. The product family includes different size globe, which enables easy replacement of most incandescent lamp all the way.

Product data

General Information	
Cap-Base	E27 [E27]
Nominal Lifetime (Nom)	10000 h
Switching Cycle	30000X
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	860 lm
Luminous Flux (Rated) (Nom)	860 lm
Color Designation	Warm White (WW)
Lumen Maintenance 2000 h (Nom)	83 %
Chromaticity Coordinate X (Nom)	463
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	55 lm/W
Color Rendering Index (Min)	81
Color Rendering Index (Nom)	82
LLMF At End Of Nominal Lifetime (Nom)	65 %
Operating and Electrical	
Input Frequency	50 or 60 Hz
Power (Rated) (Nom)	16.0 W
Lamp Current (Nom)	116 mA
Starting Time (Nom)	0.3 s

Warm Up Time to 60% Light (Min)	10 s
Warm Up Time to 60% Light (Max)	100 s
Power Factor (Nom)	0.6
Voltage (Nom)	220-240 V

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	16 kWh


Product Data	
Full product code	871150083014245
Order product name	Softone Globe 16W WW E27 G120 1CH/4
EAN/UPC - Product	8711500830142
Order code	929689151502
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	929689151502
Net Weight (Piece)	0.135 kg

Softone Globe

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Amb GL 16W WW E27 220-240V 50/60Hz G120

Product	C (max)	F (max)
Softone Globe 16W WW E27 G120 1CH/4	182 mm	48.2 mm

