PHILIPS Lighting



MASTER PL-T TOP 4 Pin

MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX

MASTER PL-T TOP is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The Philips amalgam technology guarantees optimum performance in applications with a wide temperature range, enabling significantly higher output and efficacy levels. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Product data

General Information			
Cap-Base	GX24Q-2 [GX24q-2]		
Life to 50% Failures Preheat (Nom)	13000 h		
LSF Preheat 2000 h Rated	99 %		
LSF Preheat 4000 h Rated	98 %		
LSF Preheat 6000 h Rated	97 %		
LSF Preheat 8000 h Rated	90 %		
Light Technical			
Color Code	830 [CCT of 3000K]		
Luminous Flux (Nom)	1200 lm		
Luminous Flux (Rated) (Nom)	1200 lm		
Color Designation	Warm White (WW)		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (Rated) (Min)	67 lm/W		
Color Rendering Index (Nom)	>80		
LLMF 2000 h Rated	92 %		
LLMF 4000 h Rated	88 %		
LLMF 6000 h Rated	85 %		

LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %
Operating and Electrical	
Power (Nom)	18.0 W
Lamp Current (Nom)	0.220 A
Temperature	
Design Temperature (Nom)	28 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	4 Pins
Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	1.4 mg

MASTER PL-T TOP 4 Pin

Energy Consumption kWh/1000 h	21 kWh
Product Data	
Full product code	871150088908970
Order product name	MASTER PL-T TOP 18W/830/4P 1CT/5X10BOX
EAN/UPC - Product	8711500889089
Order code	927910883069

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927910883069
Net Weight (Piece)	58.000 g
ILCOS Code	FSM-18/30/1B-E-GX24q=2

Warnings and Safety

Dimensional drawing


п

Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T TOP 18W/830/4P 1CT/	41 mm	71.7 mm	96.0 mm	111.7 mm
5X10BOX				

PL-T TOP 18W/830/4P A


Photometric data

0 ----




MASTER PL-T TOP 4 Pin

Lifetime



LDLM_PLTTOP4P_0001-Lumen maintenance diagram



LDLE_PLTTOP4P_0002-Life expectancy diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

LDLE_PLTTOP4P_0001-Life expectancy diagram