



PrimaVision Mini for CDM

HID-PV m 1x020/I mCDM LPF 220-240V

Miniature HID electronic gear for PGJ5 CDM lamps – freeing up the boundaries of creativity and innovation in luminaire design

Product data

General Information	
Application code	LPF
Type version	mk1
Lamp type	CDM
Number of lamps	1 piece/unit
Suitable for outdoor use	No
Number of products on MCB (16 A type B)	48
(nom.)	
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Minimum mains voltage operation (min.)	198 V
Operating frequency (nom.)	0.10 kHz
Ignition voltage (max.)	1.5 kV
Ignition voltage (min.)	1.3 kV
Ignition switch-off time (nom.)	25 min
Mains voltage performance (AC)	-10%-+6%
Mains voltage safety (AC)	-18%-+10%
Earth leakage current (max.)	0.25 mA
Inrush current width	0.40 ms
Constant wattage deviation	-3%/+3%


Power losses (nom.)	3 W
Inrush current peak (max.)	30 A
Wiring	
Cable capacity output wires mutual (nom.)	200 pF
Cable length from device to lamp	2 m
Wire strip length	10.0-11.0 mm
Ballast contact wire cross section	0.75-2.50 mm²
Connector type	Insert
System characteristics	
Rated ballast-lamp power	20 W
Temperature	
T ambient (max.)	50 °C
T ambient (min.)	-20 °C
T storage (max.)	80 °C
T storage (min.)	-25 ℃
T case lifetime (nom.)	65 ℃
T-Case maximum (max.)	75 °C


PrimaVision Mini for CDM

Mechanical and Housing	
Housing	/1
Approval and Application	
Active temperature protection	Yes
EMI 9 kHz 300 MHz	CISPR 15 ed 7.2
Vibration standard	IEC68-2-6 F c
Bumps standard	IEC 68-2-29 Eb
Approval marks	F-Marking CE marking CB Certificate
Humming and noise level	Inaudible
Product Data	
Full product code	871150090981730

Order product name	HID-PV m PGJ5 20 /I CDM LPF
	220-240V
EAN/UPC – product	8711500909817
Order code	90981730
Local Code	HIDPVMPGJ5020I
Numerator – quantity per pack	1
Numerator – packs per outer box	12
Material no. (12NC)	913700601666
Net weight (piece)	0.140 kg

Dimensional drawing





HID-PV m PGJ5 20 /I CDM LPF 220-240V



HID-PV m PGJ5 20 /I CDM LPF 220-240V



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2020, March 19 - data subject to change