



HID ignitors for series systems

SX 73 220-240V 50/60HZ

HID ignitors for series systems

Product data

General Information	
Application code	73
Lamp type	SOX
Number of lamps	1 piece/unit
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Parallel
Ignition voltage (max.)	1.4 kV
Response voltage	198 V
Mains voltage performance (AC)	-8%-+6%
Mains voltage safety (AC)	-10%-+10%
Power losses (nom.)	1.0 W
Wiring	
Cable capacity wires device to lamp (nom.)	5 nF
Wire strip length	6.0 mm
Ballast contact wire cross section	0.50-2.50 mm ²
Connector type	Screw


System characteristics	
Rated ballast-lamp power	180 W
Temperature	
T ambient (max.)	75 °C
T ambient (min.)	-20 °C
T storage (max.)	80 °C
T storage (min.)	-25 °C
T-Case maximum (max.)	80 °C
Mechanical and Housing	
Housing	SNI-85
Approval and Application	
Approval marks	CE marking ENEC certificate
Product Data	
Full product code	871150092005830
Order product name	SX 73 220-240V 50/60Hz
EAN/UPC – product	8711500920058
Order code	92005830
Local Code	SX73
Numerator – quantity per pack	1

Datasheet, 2020, March 19 data subject to change

HID ignitors for series systems

Numerator – packs per outer box	48
Material no. (12NC)	913700625466
Net weight (piece)	0.060 kg

Dimensional drawing



SX 73 220-240V 50/60Hz

Product

SX 73 220-240V 50/60Hz



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.