



HID ignitors for series systems

SND 57 220-240V 50/60HZ

HID ignitors for series systems

Product data

General Information	
Application code	57
Lamp type	SON
Number of lamps	1 piece/unit
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Semi-Parallel
Ignition attempts	3
Ignition time (max.)	1185 s
Ignition voltage (max.)	2.5 kV
Ignition voltage (min.)	1.8 kV
Response voltage	195 V
Mains voltage performance (AC)	-8% - +6%
Mains voltage safety (AC)	-10% - +10%
Power losses (nom.)	1.0 W
Wiring	
Ballast contact wire cross section	0.70-2.50 mm ²
Connector type	Screw


System characteristics	
Rated ballast-lamp power	50/70 W
Temperature	
T ambient (max.)	85 °C
T ambient (min.)	-20 °C
T-Case maximum (max.)	90 °C
Mechanical and Housing	
Housing	SNI-85
Approval and Application	
Approval marks	CE marking ENEC certificate
Product Data	
Full product code	871150093066830
Order product name	SND 57 220-240V 50/60Hz
EAN/UPC – product	8711500930668
Order code	93066830
Local Code	SND57
Numerator – quantity per pack	1
Numerator – packs per outer box	48
Material no. (12NC)	913700184966

HID ignitors for series systems

Net weight (piece)

0.050 kg

Dimensional drawing



SND 57 220-240V 50/60Hz

Product

SND 57 220-240V 50/60Hz

