PHILIPS Lighting



MASTER PL-C Xtra 4 Pin

MASTER PL-C Xtra 18W/840/4P 1CT/5X10BOX

MASTER PL-C Xtra is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. MASTER PL-C Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-C lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

Product data

General Information	
Cap-Base	G24Q-2 [G24q-2]
Life to 50% Failures Preheat (Nom)	33000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	96 %
LSF Preheat 16000 h Rated	94 %
LSF Preheat 20000 h Rated	90 %

840 [CCT of 4000K]
1200 lm
1200 lm
Cool White (CW)
4000 K

Luminous Efficacy (rated) (Nom)	67 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	86 %
LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %
LLMF 16000 h Rated	79 %
LLMF 20000 h Rated	78 %
Operating and Electrical	
Power (Nom)	18 W
Lamp Current (Nom)	0.220 A


MASTER PL-C Xtra 4 Pin

Temperature	
Design Temperature (Nom)	28 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	4 Pins
Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	20 kWh

Product Data	
Full product code	871150095036970
Order product name	MASTER PL-C Xtra 18W/840/4P 1CT/5X10BOX
EAN/UPC - Product	8711500950369
Order code	927906584014
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927906584014
Net Weight (Piece)	55.300 g
ILCOS Code	FSQ-18/40/1B-E-G24q=2

Warnings and Safety

Dimensional drawing




PL-C Xtra 18W/840/4P

Photometric data

Product

MASTER PL-C Xtra 18W/840/4P 1CT/5X10BOX





MASTER PL-C Xtra 4 Pin

Lifetime

Lamp survival (%)

100

90


80

70

60

50

0




Preheat start Non-preheat start


30000



10000

20000





LDLM_PLC4PLTG_0001-Lumen maintenance diagram



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2020, March 19 - data subject to change