



Softone ESaver Candle

Softone Candle 12W WW E14 220-240V 1PF/6

Elegant Energy saving lamp with decorative comfort & design, allows easy replacement of most candle shape incandescent lamp.

Product data

General Information		Lamp Current (Nom)	
Cap-Base	E14 [E14]		80 mA
Nominal Lifetime (Nom)	10000 h	Starting Time (Nom)	1.0 s
Switching Cycle	30000X	Warm Up Time to 60% Light (Min)	10 s
		Warm Up Time to 60% Light (Max)	100 s
		Power Factor (Nom)	0.6
		Voltage (Nom)	220-240 V
Light Technical		Controls and Dimming	
Color Code	827 [CCT of 2700K]	Dimmable	No
Luminous Flux (Nom)	610 lm		
Luminous Flux (Rated) (Nom)	610 lm	Approval and Application	
Color Designation	Warm White (WW)	Energy Efficiency Label (EEL)	A
Lumen Maintenance 2000 h (Nom)	83 %	Mercury (Hg) Content (Max)	2.0 mg
Chromaticity Coordinate X (Nom)	463	Mercury (Hg) Content (Nom)	1.5 mg
Chromaticity Coordinate Y (Nom)	420	Energy Consumption kWh/1000 h	12 kWh
Correlated Color Temperature (Nom)	2700 K		
Luminous Efficacy (rated) (Nom)	51 lm/W	Product Data	
Color Rendering Index (Min)	81	Full product code	871829168095600
Color Rendering Index (Nom)	82	Order product name	Softone Candle 12W WW E14 220-240V 1PF/6
LLMF At End Of Nominal Lifetime (Nom)	65 %	EAN/UPC - Product	8718291680956
		Order code	929689139501
Operating and Electrical		Numerator - Quantity Per Pack	1
Input Frequency	50 or 60 Hz		
Power (Rated) (Nom)	12.0 W		


Softone ESaver Candle

Numerator - Packs per outer box	6
Material Nr. (12NC)	929689139501
Net Weight (Piece)	0.048 kg

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Product	D (max)	C (max)	F (max)
Softone Candle 12W WW E14 220-240V 1PF/6	46.5 mm	126.0 mm	43 mm

Candle 12W/827 E14 220-240V 50/60Hz

