



CorePro LED PLC 8.5W 830 2P G24d-3

Philips CorePro LED PLC is the ideal uplamping solution for downlights in a wide range of general lighting applications. It integrates a LED light source into a traditional fluorescent form factor to offer superb energy savings over a lifetime that's twice as long as fluorescent alternatives.

Product data

General Information				
Cap base	G24D-3 [G24d-3]			
EU RoHS compliant	Yes			
Nominal lifetime (nom.)	30000 h			
Switching cycle	50000X			
Light Technical				
Colour code	830 [CCT of 3,000 K]			
Luminous flux (nom.)	950 lm			
Correlated colour temperature (nom.)	3000 K			
Colour consistency	<6			
Color rendering index (nom.)	83			
LLMF at end of nominal lifetime (nom.) 70 %				
Operating and Electrical				
Input frequency	50 to 60 Hz			
Power (Rated) (Nom)	8.5 W			
Lamp current (max.)	43 mA			
Lamp current (min.)	33 mA			
Starting time (nom.)	0.5 s			
Warm-up time to 60% light (nom.)	0.5 s			
Power factor (nom.)	0.9			


Voltage (Nom)	220-240 V			
Temperature				
T ambient (max.)	35 ℃			
T ambient (min.)	-20 °C			
T storage (max.)	65 ℃			
T storage (min.)	-40 °C			
T-Case maximum (nom.)	75 ℃			
Controls and Dimming				
Dimmable	no			
Mechanical and Housing				
Product length	200 mm			
Approval and Application				
Energy efficiency label (EEL)	A+			
Energy-saving product	Yes			
Approval marks	CE marking RoHS compliance KEMA Keur			
	certificate			
Energy Consumption kWh/1000 h	11 kWh			

Datasheet, 2020, March 24 data subject to change

Product Data	
Full product code	871869654123400
Order product name	CorePro LED PLC 8.5W 830 2P G24d-3
EAN/UPC – product	8718696541234
Order code	54123400
Numerator – quantity per pack	1

Numerator – packs per outer box	10
Material no. (12NC)	929001201202
Net weight (piece)	0.090 kg


Dimensional drawing



LEDtube PLC 8.5W G24d-3/830 2P


Product	D1	D2	A1	A2	А3
CorePro LED PLC 8.5W 830	24.3 mm	28.4 mm	128.8 mm	148 mm	170.6 mm
2P G24d-3					

Photometric data





Calculat Photomerica 43 Philips Lighting RV. Pages 37

LEDtube PLC 100mm 9W G24D-3 830 950lm




Lifetime





LEDtube PLC 100mm 9W G24D-3 830 950lm

LEDtube PLC 100mm 9W G24D-3 830 950lm



LEDtube PLC 100mm 9W G24D-3 830 950lm

LEDtube PLC 100mm 9W G24D-3 830 950lm

LEDtube PLC 100mm 9W G24D-3 830 950lm



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.