



Softone Flame

Softone Flame Candle 8W E14 B40 1PF/6

High quality flame colored energy saving lamps which is decoratively shaped to complement your luminaire.

Product data

General Information	
Cap-Base	E14 [E14]
Nominal Lifetime (Nom)	10000 h
Switching Cycle	30000X
Light Technical	
Luminous Flux (Nom)	320 lm
Luminous Flux (Rated) (Nom)	320 lm
Color Designation	Flame
Lumen Maintenance 2000 h (Nom)	83 %
Chromaticity Coordinate X (Nom)	463
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2200 K
Luminous Efficacy (rated) (Nom)	46 lm/W
Color Rendering Index (Min)	80
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	65 %
Operating and Electrical	
Input Frequency	50 or 60 Hz
Power (Rated) (Nom)	8.0 W
Lamp Current (Nom)	60 mA
Starting Time (Nom)	1.5 s
Warm Up Time to 60% Light (Min)	10 s

Warm Up Time to 60% Light (Max)	100 s
Power Factor (Nom)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	No
Approval and Application	
Energy Efficiency Label (EEL)	B
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	8 kWh


Product Data	
Full product code	872790090522902
Order product name	Softone Flame Candle 8W E14 B40 1PF/6
EAN/UPC - Product	8727900905229
Order code	929689199201
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929689199201
Net Weight (Piece)	46.000 g

Softone Flame

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Product	D (max)	C (max)	F (max)
Softone Flame Candle 8W E14 B40 1PF/6	41.5 mm	120.5 mm	39 mm

Candle 8W Flame E14 220-240V 50/60Hz

