



# MSR

## MSR 1200 1CT/3

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

### Product data

General Information	
Cap-Base	G22 [ G22]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Main Application	Studio/Disco
Life to 50% Failures (Nom)	800 h
System Description	Cold Strike
Light Technical	
Color Code	- [ Not Specified]
Luminous Flux (Min)	94000 lm
Luminous Flux (Nom)	110000 lm
Chromaticity Coordinate X (Nom)	325
Chromaticity Coordinate Y (Nom)	320
Correlated Color Temperature (Nom)	5900 K
Luminous Efficacy (rated) (Nom)	91 lm/W
Color Rendering Index (Nom)	80
Operating and Electrical	
Power (Nom)	1200 W
Lamp Current (Nom)	13.8 A


Ignition Supply Voltage (Min)	207 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	30 mm x 53 mm
Luminaire Design Requirements	
Bulb Temperature (Max)	700 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	872790091121300
Order product name	MSR 1200 1CT/3
EAN/UPC - Product	8727900911213
Order code	928078105114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	928078105114

# MSR

Net Weight (Piece)	0.150 kg
--------------------	----------

## Warnings and Safety

## Dimensional drawing



MSR 1200

## Product

MSR 1200 1CT/3

## Photometric data

