



Architectural MSD

MSD 575 1CT/16

The high luminous efficacy and optimal lamp filling of the single ended Architectural MSD lamps create high beam intensity and excellent color rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

Product data

General Information	
Cap-Base	GX9.5 [GX9.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Studio/Disco
Life to 50% Failures (Nom)	3000 h
System Description	-

Light Technical	
Color Code	- [Not Specified]
Luminous Flux (Min)	38700 lm
Luminous Flux (Nom)	43000 lm
Chromaticity Coordinate X (Nom)	323
Chromaticity Coordinate Y (Nom)	317
Correlated Color Temperature (Nom)	6000 K
Luminous Efficacy (Rated) (Min)	68 lm/W
Luminous Efficacy (rated) (Nom)	75 lm/W
Color Rendering Index (Nom)	72

Operating and Electrical	
Power (Nom)	575 W
Lamp Current (Nom)	7.6 A
Ignition Supply Voltage (Min)	207 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Cap-Base Information	-

Luminaire Design Requirements	
Bulb Temperature (Max)	700 °C
Pinch Temperature (Max)	350 °C

Product Data	
Full product code	872790091755000
Order product name	MSD 575 1CT/16
EAN/UPC - Product	8727900917550
Order code	928098805114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	928098805114
Net Weight (Piece)	0.062 kg

Architectural MSD

Warnings and Safety

Dimensional drawing

D

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD 575	30 mm	8.0	64 mm	66 mm	65	125 mm	36 mm	35	34 mm
1CT/16		mm			mm			mm	

MSD 575

Photometric data

