

## Product information sheet

### LED Bulkhead Basic 6W 420lm 4000K Oval Black

Bailey nr.: 139759

EAN-code: 8714681397596

#### Type of light source

Lighting technology used	LED
Cap type	Screwed terminal
Non-directional or directional	DLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No

#### Specifications

Energy consumption in on-mode (KWh/1000h)	6
Energy Efficiency Class	G
Useful luminous flux (use) in lm	420
Beam angle correspondence	Wide cone (120°)
Correlated colour temperature (K)	4000
On-mode power (Pon) in W	6,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	167
Outer dimensions (Width) in mm	116
Outer dimensions (Depth) in mm	72
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,382
Chromaticity coordinate (y)	0,380
Peak luminous intensity (cd)	120
Beam angle (°)	120
R9 Colour rendering index	0
Survival factor	0,90
Lumen maintenance factor	0,96
Displacement factor	0,70
Colour consistency in McAdam ellipses	6
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	1,0
Stroboscopic effect metric	0,4
Lifetime L70B50 (h)	10000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50



Specific precautions

N/A

Spectral power distribution

