

## Product information sheet

### RoBust LED Portable 2.0 20W 4000K

Bailey nr.: 140794

EAN-code: 8714681407943

#### Type of light source

Lighting technology used	LED
Cap type	-
Non-directional or directional	DLS
Mains or non-mains	Battery
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes

#### Specifications

Energy consumption in on-mode (KWh/1000h)	20
Energy Efficiency Class	N/A
Useful luminous flux (use) in lm	1600
Beam angle correspondence	Wide cone (120°)
Correlated colour temperature (K)	4000
On-mode power (Pon) in W	20,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	210
Outer dimensions (Width) in mm	184
Outer dimensions (Depth) in mm	77
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	-
Beam angle (°)	-
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	30000
Nominal voltage (V)	-
Voltage type	-
Frequency	-



Specific precautions N/A

Spectral power distribution