

## Product information sheet

### LED Party T8 29X1500 G13 22W (58W) Red EM+AC

Bailey nr.: 141892

EAN-code: 8714681418925

#### Type of light source

|                                |      |
|--------------------------------|------|
| Lighting technology used       | LED  |
| Cap type                       | G13  |
| Non-directional or directional | NDLS |
| Mains or non-mains             | MLS  |
| Connected light source (CLS)   | No   |
| Colour-tuneable light source   | No   |
| Envelope                       | No   |
| High luminance light source    | No   |
| Anti-glare shield              | No   |
| Dimmable                       | No   |



#### Specifications

|   |               |
|---|---------------|
| Energy consumption in on-mode (KWh/1000h)   | 22            |
| Energy Efficiency Class                     | G             |
| Useful luminous flux (use) in lm            | 370           |
| Beam angle correspondence                   | Sphere (360°) |
| Correlated colour temperature (K)           | Red           |
| On-mode power (Pon) in W                    | 22,0          |
| Standby power (Psb) in W                    | 0,00          |
| Networked standby power for CLS (Pnet) in W | -             |
| Colour rendering index                      | N/A           |
| Outer dimension (Height) in mm              | 1500          |
| Outer dimensions (Width) in mm              | 29            |
| Outer dimensions (Depth) in mm              | -             |
| Claim of equivalent power                   | No            |
| Equivalent power (W)                        | -             |
| Chromaticity coordinate (x)                 | 0,710         |
| Chromaticity coordinate (y)                 | 0,295         |
| Peak luminous intensity (cd)                | N/A           |
| Beam angle (°)                              | 280           |
| R9 Colour rendering index                   | -             |
| Survival factor                             | -             |
| Lumen maintenance factor                    | -             |
| Displacement factor                         | 0,90          |
| Colour consistency in McAdam ellipses       | -             |
| Claim CFL-ni                                | No            |
| Replacement claim (W)                       | -             |
| Flicker metric                              | -             |
| Stroboscopic effect metric                  | -             |
| Lifetime L70B50 (h)                         | 25000         |
| Nominal voltage (V)                         | 220-240       |
| Voltage type                                | AC            |
| Frequency                                   | 50/60         |

Specific precautions

Disconnecting magnetic ballast is optional, not necessary. Replace the fluorescent starter with the LED starter (included).

Spectral power distribution