

Product information sheet

LED Party T8 29X1500 G13 22W (58W) Green EM+AC

Bailey nr.: 141895

EAN-code: 8714681418956

Type of light source

Lighting technology used	LED
Cap type	G13
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No

Specifications

Energy consumption in on-mode (KWh/1000h)	22
Energy Efficiency Class	G
Useful luminous flux (use) in lm	1200
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	Green
On-mode power (Pon) in W	22,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	N/A
Outer dimension (Height) in mm	1500
Outer dimensions (Width) in mm	29
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,180
Chromaticity coordinate (y)	0,700
Peak luminous intensity (cd)	N/A
Beam angle (°)	280
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	0,90
Colour consistency in McAdam ellipses	-
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	-
Stroboscopic effect metric	-
Lifetime L70B50 (h)	25000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60



Specific precautions

Disconnecting magnetic ballast is optional, not necessary. Replace the fluorescent starter with the LED starter (included).

Spectral power distribution