

Product information sheet

LED Spot MR11 GU4 12V 4.5W (20W) 270lm 927 32D

Bailey nr.: 141981

EAN-code: 8714681419816

Type of light source

Lighting technology used	LED
Cap type	GU4
Non-directional or directional	DLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No

Specifications

Energy consumption in on-mode (KWh/1000h)	5
Energy Efficiency Class	G
Useful luminous flux (use) in lm	270
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2700
On-mode power (Pon) in W	4,5
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	90
Outer dimension (Height) in mm	37
Outer dimensions (Width) in mm	34
Outer dimensions (Depth) in mm	-
Claim of equivalent power	Yes
Equivalent power (W)	20
Chromaticity coordinate (x)	0,464
Chromaticity coordinate (y)	0,408
Peak luminous intensity (cd)	802
Beam angle (°)	32
R9 Colour rendering index	50
Survival factor	1,00
Lumen maintenance factor	0,96
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	40000
Nominal voltage (V)	12
Voltage type	AC/DC
Frequency	-



Specific precautions N/A

Spectral power distribution

